

BRIDGESTONE

DUELER A/T REVO 3



ENGINEERED TO PERFORM FOR YOUR ACTIVE LIFESTYLE

FEATURES AND BENEFITS

-  Better off-road handling*
-  Long-lasting performance*
-  Improved wet and snow performance*
-  Quiet, comfortable ride

Up to

60000

Limited Mileage Warranty†

Up to

1000000

Kilometer Treadwear Warranty

*Vs. the Bridgestone Dueler A/T Revo 2.
†60,000 mile limited mileage warranty for non-LT sizes, 50,000 mile limited mileage warranty for LT sizes. Certain conditions and limitations apply. See a Bridgestone representative or BridgestoneTire.com for details.

1 STAGGERED SHOULDER LUGS

for extra biting edges in soft, irregular surfaces

2 GROOVE STEPPING

stiffens tread blocks for enhanced wear life and traction performance

3 AGGRESSIVE NEW PATTERN WITH TRACTION CLAWS

provide additional grip in off-road and snow conditions

4 OPEN SHOULDER SLOTS AND 3D STEPS

help water evacuation and add traction to shoulder edges



SIZE	SERVICE DESCRIPTION SGL/DUAL	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
16" RIM DIAMETER												
P225/75R16	104T	---	000056	OWL	6.0-7.5	6.0	29.3	8.8	12	711	540 A B	30.0
LT245/75R16	120/116S	E	000016	OWL	6.5-8.0	7.0	30.5	9.8	14	684	N/A	40.1
P245/75R16	109T	---	000037	OWL	6.5-8.0	7.0	30.5	9.8	12	684	540 A B	36.6
LT265/75R16	123/120R	E	000020	OWL	7.0-8.0	7.5	31.7	10.5	15	658	N/A	44.7
P265/75R16	114T	---	000036	OWL	7.0-9.0	7.5	31.7	10.5	13	658	540 A B	39.3
LT285/75R16	126/123R	E	000025	OWL	7.5-9.0	8.0	32.8	11.3	16	634	N/A	50.7
P265/70R16	111T	---	000041	OWL	7.0-9.0	8.0	30.6	10.7	13	680	540 A B	38.1
17" RIM DIAMETER												
LT245/75R17	121/118R	E	000017	OWL	6.5-7.5	7.0	31.5	9.8	14	661	N/A	42.0
LT255/75R17	111/108R	C	000018	OWL	6.5-8.5	7.0	32.1	10.0	15	650	N/A	40.9
P245/70R17	108T	---	000044	OWL	6.5-8.0	7.0	30.6	9.8	12	682	540 A B	35.9
LT265/70R17	121/118S	E	000019	OWL	7.0-8.5	8.0	31.7	10.7	15	658	N/A	45.7
P265/70R17	113T	---	000033	OWL	7.0-9.0	8.0	31.7	10.7	13	658	540 A B	39.6
LT285/70R17	121/118R	E	000024	OWL	7.5-9.0	8.5	32.8	11.5	16	636	N/A	50.2
P285/70R17	117T	---	000038	OWL	7.5-9.5	8.5	32.8	11.5	13	636	540 A B	43.8
LT315/70R17	121/118S	E	000026	OWL	8.5-10.0	9.5	34.4	12.7	17	605	N/A	59.2
P245/65R17	105T	---	000032	OWL	7.0-8.5	7.0	29.5	9.8	12	705	540 A B	34.9
P265/65R17	110T	---	000042	OWL	7.5-9.5	8.0	30.6	10.7	12	682	540 A B	39.1
18" RIM DIAMETER												
P255/70R18	112T	---	000049	OWL	6.5-8.5	7.5	32.1	10.2	13	649	540 A B	39.5
LT265/70R18	124/121R	E	000029	OWL	7.0-9.0	8.0	32.6	10.7	15	638	N/A	48.1
P265/70R18	114T	---	000040	OWL	7.0-9.0	8.0	32.6	10.7	13	638	540 A B	41.9
LT275/70R18	125/122S	E	000027	OWL	7.0-8.5	8.0	33.2	11.0	16	628	N/A	50.2
LT295/70R18	129/126S	E	007116	BW	7.5-10.0	8.5	34.3	11.8	16	607	N/A	55.0
P265/65R18	112T	---	000050	OWL	7.5-9.5	8.0	31.5	10.7	13	660	540 A B	40.8
LT275/65R18	123/120S	E	000021	BW	7.5-9.0	8.0	32.1	11.0	16	649	N/A	47.9
P275/65R18	114T	---	000043	OWL	7.5-9.5	8.0	32.1	11.0	13	649	540 A B	41.9
LT285/65R18	125/122S	E	007115	BW	8.0-10.0	8.5	32.6	11.5	16	640	N/A	49.8
265/60R18	110T	---	000051	OWL	7.5-9.5	8.0	30.5	10.7	12	683	540 A B	40.0
20" RIM DIAMETER												
LT275/65R20	126/123S	E	000022	BW	7.5-9.5	8.0	34.1	11.0	16	611	N/A	51.9
LT265/60R20	121/118R	E	000028	BW	7.5-9.5	8.0	32.5	10.7	15	641	N/A	47.1
P275/60R20	114T	---	000052	OWL	7.5-9.5	8.0	33.0	11.0	12	631	540 A B	41.7
LT285/60R20	125/122R	E	004284	BW	8.0-10.0	8.5	33.5	11.5	16	623	N/A	53.2
LT275/55R20	120/117S	E	007112	BW	7.5-9.5	8.5	31.9	11.2	16	653	N/A	48.7
P275/55R20	111T	---	000053	BW	7.5-9.5	8.5	31.9	11.2	12	653	540 A B	39.9
LT285/55R20	122/119S	E	007113	BW	8.0-10.0	9.0	32.4	11.7	15	644	N/A	52.0
LT305/55R20	121/118S	E	007114	BW	8.5-11.0	9.5	33.2	12.4	15	627	N/A	54.2
265/50R20	107T	---	004282	BW	7.5-9.5	8.5	30.5	10.9	12	684	540 A B	37.6