

CROSSCONTACT LX²⁵







Aspect Ratio



16" - 22

45 - 70

Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED			
740	А	В	Т			
740	A	A	H & V			



Benefits

- Expanded size lineup covering speed ratings from T through V
- Best-in-class tread life*
- Improved wet braking**
- · Low road noise
- Responsive handling





- Saves fuel & optimizes range
- Stops shorter on wet roads
- Extends tread life



Tuned Performance Indicators

D, W and S symbols in the tread disappear when the tire is no longer tuned for optimum performance in either dry (D), wet (W) or snow (S) conditions.



Alignment Verification System

Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.



EV Compatible

All Continental product lines are designed with Electric Vehicles (EVs) in mind and are optimized for the needs of all types of vehicles.

Sample Vehicle Fitments Include:

- Acura RDX
- Chevrolet Equinox
- Ford: Edge, Explorer
- Honda: CR-V, Pilot
- Jeep Grand Cherokee
- Kia Telluride
- Lexus RX
- Mazda CX-5
- Toyota: Highlander, RAV4
- Volkswagen Tiguan



^{**}Compared to the CrossContact LX20, in the size 235/60R18 H.



The purchase of replacement Continental tires provides an extra measure of confidence with the Total Confidence Plan.

Restrictions and limitations apply. See Total Confidence Plan for complete coverage details at https://continentaltire.com/warranty.



Road Hazard Coverage¹









Up to 70,000 Mileage Warranty²



Flat Tire Roadside Assistar



Emergency Trip Interruption Coverage

- ¹ Coverage is within the first 12 months from the date of purchase or the first 2/32^{nds} treadwear, whichever comes first whichever comes first. Repairable conditions are not eligible for replacement.
- Mileage warranty for the rear axle of split fitments will be 50% of standard tread wearout coverage.

CROSSCONTACT LX²⁵ | Product Data

CROSSOVER/LIGHT TRUCK/SUV TIRES | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/ SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE
16	70	215/70 R 16	100 H	SL	BSW	15509680000	Yes	27.9	25.9	51.0	8.7 (6.5)	(5.5 - 7.0)	1764	12	746
	70	215/70 R 16	100 T	SL	BSW	15571310000	Yes	27.9	25.5	44.0	8.7 (6.5)	(5.5 - 7.0)	1764	12	746
	70	235/70 R 16	106 T	SL	OWL	15509920000	Yes	29.0	31.7	44.0	9.4 (7.0)	(6.0 - 8.0)	2094	12	718
	55	225/55 R 17	97 H	SL	BSW	15571320000	Yes	26.7	25.1	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	12	777
17	55	235/55 R 17	99 H	SL	BSW	15571330000	Yes	27.2	28.3	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	12	764
	60	225/60 R 17	99 H	SL	BSW	15571430000	Yes	27.6	29.1	51.0	9.0 (6.5)	(6.0 - 8.0)	1709	12	752
	60	235/60 R 17	102 H	SL	BSW	15448390000	Yes	28.1	27.6	51.0	9.4 (7.0)	(6.5 - 8.5)	1874	12	739
	65	225/65 R 17	102 H	SL	BSW	15509980000	Yes	28.5	27.0	51.0	9.0 (6.5)	(6.0 - 8.0)	1874	12	729
	65	225/65 R 17	102 T	SL	BSW	15571450000	Yes	28.5	27.3	44.0	9.0 (6.5)	(6.0 - 8.0)	1874	12	729
	65	235/65 R 17	108 H	XL	BSW	15447860000	Yes	29.0	30.0	51.0	9.4 (7.0)	(6.5 - 8.5)	2205	12	716
	65	245/65 R 17	107 T	SL	OWL	15447950000	Yes	29.5	34.0	44.0	9.8 (7.0)	(7.0 - 8.5)	2149	12	703
	50	235/50 R 18	97 H	SL	BSW	15571370000	Yes	27.3	27.8	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	12	762
	55	215/55 R 18	95 H	SL	BSW	15571340000	Yes	27.3	25.2	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	12	761
	55	225/55 R 18	98 H	SL	BSW	15571360000	Yes	27.7	27.9	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	12	749
18	55	235/55 R 18	100 H	SL	BSW	15491450000	Yes	28.2	27.8	51.0	9.6 (7.5)	(6.5 - 8.5)	1764	12	737
	55	235/55 R 18	100 T	SL	BSW	15491480000	Yes	28.2	27.0	44.0	9.6 (7.5)	(6.5 - 8.5)	1764	12	737
	55	255/55 R 18	109 H	XL	BSW	15491440000	Yes	29.0	36.0	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	12	715
	60	225/60 R 18	100 H	SL	BSW	15491370000	Yes	28.6	25.4	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	12	726
	60	235/60 R 18	103 H	SL	BSW	15491380000	Yes	29.1	31.8	51.0	9.4 (7.0)	(6.5 - 8.5)	1929	12	714
	60	235/60 R 18	107 V	XL	BSW	15491390000	Yes	29.1	29.9	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	10	714
	60	245/60 R 18	105 H	SL	BSW	15491400000	Yes	29.6	32.0	51.0	9.8 (7.0)	(7.0 - 8.5)	2039	12	702
	60	245/60 R 18	105 T	SL	BSW	15491410000	Yes	29.6	31.2	44.0	9.8 (7.0)	(7.0 - 8.5)	2039	12	702
	60	245/60 R 18	105 V	SL	BSW	15571810000	Yes	29.6	30.4	51.0	9.8 (7.0)	(7.0 - 8.5)	2039	11	702
	60	255/60 R 18	112 V	XL	BSW	15578770000	Yes	30.0	36.1	50.0	10.2 (7.5)	(7.0 - 9.0)	2469	11	691
	60	265/60 R 18	110 H	SL	BSW	15491430000	Yes	30.5	38.5	51.0	10.7 (8.0)	(7.5 - 9.5)	2337	12	681
	65	235/65 R 18	106 H	SL	BSW	15491330000	Yes	30.0	30.3	51.0	9.4 (7.0)	(6.5 - 8.5)	2094	12	692
	65	235/65 R 18	106 T	SL	BSW	15491320000	Yes	30.0	30.3	44.0	9.4 (7.0)	(6.5 - 8.5)	2094	12	692
	65	255/65 R 18	111 T	SL	BSW	15491340000	Yes	31.1	36.4	44.0	10.2 (7.5)	(7.0 - 9.0)	2403	12	669
	65	255/65 R 18	111 H	SL	BSW	15571950000	Yes	31.1	38.8	51.0	10.2 (7.5)	(7.0 - 9.0)	2403	12	669
	50	235/50 R 19	99 H	SL	BSW	15491590000	Yes	28.3	28.7	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	12	735
	50	245/50 R 19	105 H	XL	BSW	15572000000	Yes	28.6	31.0	51.0	10.0 (7.5)	(7.0 - 8.5)	2039	12	725
	50	255/50 R 19	107 H	XL	BSW	15491600000	Yes	29.0	34.0	51.0	10.4 (8.0)	(7.0 - 9.0)	2149	12	715
	55	225/55 R 19	99 V	SL	BSW	15491500000	Yes	28.7	26.6	51.0	9.2 (7.0)	(6.0 - 8.0)	1709	10	723
19	55	235/55 R 19	101 H	SL	BSW	15491550000	Yes	29.2	30.1	51.0	9.6 (7.5)	(6.5 - 8.5)	1819	12	712
	55	235/55 R 19	105 V	XL	BSW	15491510000	Yes	29.2	28.8	51.0	9.6 (7.5)	(6.5 - 8.5)	2039	10	712
	55	245/55 R 19	103 H	SL	BSW	03640150000	Yes	29.6	31.4	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	12	702
	55	275/55 R 19	111 H	SL	BSW	15491570000	Yes	30.9	38.4	51.0	11.2 (8.5)	(7.5 - 9.5)	2403	12	672
	60	255/60 R 19	109 H	SL	BSW	15491490000	Yes	31.0	38.4	51.0	10.2 (7.5)	(7.0 - 9.0)	2271	12	669
20	45	265/45 R 20	108 H	XL	BSW	15492500000	Yes	29.4	34.3	51.0	10.5 (9.0)	(8.5 - 10.0)	2205	12	707
	45	275/45 R 20	110 V	XL	BSW	15571390000	Yes	29.7	33.2	51.0	10.7 (9.0)	(8.5 - 10.5)	2337	10	698
	45	285/45 R 20	112 H	XL	BSW	15578780000	Yes	30.1	39.7	50.0	11.2 (9.5)	(9.0 - 10.5)	2469	12	690
	50	245/50 R 20	102 H	SL	BSW	15492310000	Yes	29.6	31.2	51.0	10.0 (7.5)	(7.0 - 8.5)	1874	12	701



CROSSCONTACT LX²⁵ | Product Data

CROSSOVER/LIGHT TRUCK/SUV TIRES | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/ SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE
20	50	265/50 R 20	107 T	SL	BSW	15492440000	Yes	30.4	34.6	44.0	10.9 (8.5)	(7.5 - 9.5)	2149	12	683
	50	265/50 R 20	107 V	SL	BSW	15578810000	Yes	30.4	36.2	51.0	10.9 (8.5)	(7.5 - 9.5)	2149	11	683
	50	275/50 R 20	109 H	SL	BSW	15492490000	Yes	30.8	38.3	51.0	11.2 (8.5)	(7.5 - 9.5)	2271	12	674
	55	235/55 R 20	102 H	SL	BSW	15491650000	Yes	30.2	30.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1874	12	688
	55	235/55 R 20	102 V	SL	BSW	15571380000	Yes	30.2	28.3	51.0	9.6 (7.5)	(6.5 - 8.5)	1874	10	688
22	45	285/45 R 22	114 H	XL	BSW	15492530000	Yes	32.1	39.8	51.0	11.2 (9.5)	(9.0 - 10.5)	2601	12	647

BSW = Black Sidewall