



PASSENGER & CROSSOVER | ALL-SEASON | TOURING

PURECONTACT™ LS

Rim Diameter



16" - 20"

Aspect Ratio



40 - 60

Tread Pattern



Asymmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	LOAD INDEX
700	A	A	H & V	--

INCLUDES
70K
MILEAGE
WARRANTY

Benefits

- Best-in-class wet braking*
- Exceptional tread life
- Optimal traction in light snow
- Low road noise


ECOPLUS+ TECHNOLOGY

- Saves fuel
- Stops shorter on wet roads
- Extends tread life




Tuned Performance Indicators

D, W and S symbols in the tread disappear when the tire is no longer tuned for optimum performance in either dry (D), wet (W) or snow (S) conditions.



Alignment Verification System

Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.



Sample Vehicle Fitments Include:

- Acura: TL, RDX, MDX
- Cadillac: DTS, STS
- Infiniti: G35, G37, Q45
- Lexus: ES, GS, LS
- Lincoln: MKZ, LS

*Based on internal wet braking results Continental PureContact LS size 245/45R18 vs. Michelin Premier A/S size 245/45R18, Pirelli Cinturato P7 A/S Plus size 245/45R18. Wet braking results on both low mu and high mu values. On road results may vary.



The purchase of replacement Continental tires provides an extra measure of confidence with the Total Confidence Plan.

Restrictions and limitations apply. See Total Confidence Plan for complete coverage details at <https://continentaltire.com/warranty>.



Road Hazard Coverage



72-Month Limited Warranty



60-Day Customer Satisfaction Trial¹



70,000 Mileage Warranty²



Flat Tire Roadside Assistance



Emergency Trip Interruption Coverage

¹ Coverage is within the stated duration from the date of purchase or the first 2/32^{nds} treadwear, whichever comes first.

² Mileage warranty for the rear axle of split fitments will be 50% of standard tread wearout coverage.

PURECONTACT™ LS | Product Data

PASSENGER/CROSSOVER TIRES | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
16	55	195/55 R 16	87 V	SL	BSW	15509360000	Yes	24.4	18.6	51.0	7.9 (6.0)	(5.5 - 7.0)	1201	10	850
	55	205/55 R 16	91 V	SL	BSW	15508060000	Yes	24.9	20.2	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	10	835
	60	205/60 R 16	92 V	SL	BSW	15508120000	No	25.7	19.6	51.0	8.2 (6.0)	(5.5 - 7.5)	1389	10	809
	60	215/60 R 16	95 V	SL	BSW	15508210000	No	26.2	21.7	51.0	8.7 (6.5)	(6.0 - 7.5)	1521	10	794
17	45	225/45 R 17	91 H	SL	BSW	15508230000	Yes	25.0	22.2	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	832
	45	225/45 R 17	91 V	SL	BSW	15508240000	Yes	25.0	22.2	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	832
	45	235/45 R 17	94 H	SL	BSW	15508370000	Yes	25.3	23.3	51.0	9.3 (8.0)	(7.5 - 9.0)	1477	10	820
	45	235/45 R 17	97 V	XL	BSW	15509200000	Yes	25.3	23.3	51.0	9.3 (8.0)	(7.5 - 9.0)	1609	10	820
	45	245/45 R 17	99 V	XL	BSW	15508810000	Yes	25.7	24.4	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	10	809
	50	205/50 R 17	93 V	XL	BSW	15508050000	Yes	25.1	20.6	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	10	829
	50	215/50 R 17	95 V	XL	BSW	15508130000	Yes	25.5	21.6	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	10	816
	50	225/50 R 17	98 V	XL	BSW	15508300000	Yes	25.9	23.2	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	10	803
	50	235/50 R 17	96 V	SL	BSW	15508440000	Yes	26.3	23.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1565	10	791
	50	245/50 R 17	99 V	SL	BSW	15508860000	Yes	26.6	26.6	51.0	10.0 (7.5)	(7.0 - 8.5)	1709	10	780
	55	215/55 R 17	94 V	SL	BSW	15508150000	Yes	26.3	22.1	51.0	8.9 (7.0)	(6.0 - 7.5)	1477	10	790
	55	225/55 R 17	97 V	SL	BSW	15508310000	Yes	26.7	23.7	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	10	777
18	40	225/40 R 18	92 V	XL	BSW	15509180000	Yes	25.1	21.1	51.0	9.1 (8.0)	(7.5 - 9.0)	1389	10	828
	40	245/40 R 18	97 V	XL	BSW	15508790000	Yes	25.7	24.7	51.0	9.8 (8.5)	(8.0 - 9.5)	1609	10	808
	45	225/45 R 18	91 V	SL	BSW	15508280000	Yes	26.0	23.8	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	800
	45	235/45 R 18	94 V	SL	BSW	15508400000	Yes	26.3	24.8	51.0	9.3 (8.0)	(7.5 - 9.0)	1477	10	789
	45	245/45 R 18	100 V	XL	BSW	15508820000	Yes	26.7	26.1	51.0	9.6 (8.0)	(7.5 - 9.0)	1764	10	779
	50	235/50 R 18	97 V	SL	BSW	15508770000	Yes	27.3	24.6	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	10	762
	50	245/50 R 18	100 V	SL	BSW	15509140000	Yes	27.6	26.9	51.0	10.0 (7.5)	(7.0 - 8.5)	1764	10	751
	55	235/55 R 18	100 V	SL	BSW	15508780000	Yes	28.2	25.6	51.0	9.6 (7.5)	(6.5 - 8.5)	1764	10	737
19	40	235/40 R 19	96 V	XL	BSW	15509190000	Yes	26.4	22.7	51.0	9.5 (8.5)	(8.0 - 9.5)	1565	10	787
	40	245/40 R 19	98 V	XL	BSW	15508800000	Yes	26.7	25.1	51.0	9.8 (8.5)	(8.0 - 9.5)	1653	10	778
	45	245/45 R 19	102 V	XL	BSW	15509350000	Yes	27.7	26.9	51.0	9.6 (8.0)	(7.5 - 9.0)	1874	10	750
	45	255/45 R 19	100 V	SL	BSW	15509150000	Yes	28.0	27.5	51.0	10.0 (8.5)	(8.0 - 9.5)	1764	10	741
20	45	245/45 R 20	99 V	SL	BSW	15508830000	Yes	28.7	26.5	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	10	724

BSW = Black Sidewall

