

CROSSOVER & LT/SUV | ALL-SEASON | ALL-TERRAIN

TERRAINCONTACT A/T

Rim Diameter







16" - 22

45 - 80

Symmetric

-	TREADWEAR	TRACTION	TEMPERATURE	SPEED		
	680	A	В	S & T (Metric)		
	680	А	А	H & V (Metric)		
				S (LT)		

INCLUDES 60K MILEAGE WARRANTY

Benefits

- Full product lineup with 22 metric and 15 LT-metric sizes
- Best-in-class wet braking*
- Balanced off-road traction with on-road manners
- Quieter than a leading competitor**
- Robust durability





- Improves traction and durability
- Grips better on wet roads
- Quiets road noise



EV Compatible

All Continental product lines are designed with Electric Vehicles (EVs) in mind and are optimized for the needs of all types of vehicles.

Sample Vehicle Fitments Include:

- Chevrolet: Colorado, Silverado, Silverado HD, Suburban, Tahoe
- Ford: Bronco, Expedition, F-150, Super Duty
- Jeep: Gladiator, Grand Cherokee, Wrangler
- Land Rover: LR3, LR4, Range Rover
- Nissan: Armada, Titan, Titan XD
- Porsche Cayenne
- Ram: 1500, 2500, 3500
- Subaru: Crosstrek, Forester
- Toyota: 4Runner, FJ Cruiser, Tundra

^{**}Based on internal noise test results Continental TerrainContact A/T size 265/70R16 vs. Michelin Defender LTX M/S size 265/70R16



The purchase of replacement Continental tires provides an extra measure of confidence with the Total Confidence Plan.

Restrictions and limitations apply. See Total Confidence Plan for complete coverage details at https://continentaltire.com/warranty.



Road Hazard Coverage¹













Emergency Trip Interruption Coverage

- ¹ Coverage is within the first 12 months from the date of purchase or the first 2/32^{nds} treadwear, whichever comes first whichever comes first. Repairable conditions are not eligible for replacement.
- Mileage warranty for the rear axle of split fitments will be 50% of standard tread wearout coverage.

^{*}Based on internal wet braking test results Continental TerrainContact A/T size 265/70R16 vs. Michelin LTX A/T2 size 265/70R16, Goodyear Wrangler All-Terrain Adventure with Kevlar size 265/70R16 and Bridgestone Dueler A/T Revo 2 size 265/70R17. Wet braking is the average of low μ and high μ values. On road results may vary.

TERRAINCONTACT A/T | Product Data

CROSSOVER/LIGHT TRUCK/SUV TIRES | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	RATIO	TIRE SIZE	LOAD/ SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE
	70	265/70 R 16	112 T	SL	OWL	15506770000	Yes	30.6	38.6	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	12	679
	75	LT245/75 R 16	120/116 S	Е	OWL	15506580000	Yes	30.5	51.0	80.0	9.8 (7.0)	(6.5 - 8.0)	3086	16	682
16	75	265/75 R 16	116 T	SL	OWL	15506790000	Yes	31.6	41.6	44.0	10.5 (7.5)	(7.0 - 9.0)	2756	12	656
	75	LT265/75 R 16	123/120 S	E	OWL	15506590000	Yes	31.6	53.2	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	16	656
	75	LT285/75 R 16	126/123 S	E	OWL	15506600000	Yes	32.8	59.1	80.0	11.3 (8.0)	(7.5 - 9.0)	3750	16	633
	60	225/60 R 17	99 H	SL	BSW	15507870000	Yes	27.6	27.6	51.0	9.0 (6.5)	(6.0 - 8.0)	1709	12	752
	65	245/65 R 17	107 T	SL	OWL	15506800000	Yes	29.5	34.3	44.0	9.8 (7.0)	(7.0 - 8.5)	2149	12	703
	65	255/65 R 17	110 S	SL	BSW	15570200000	Yes	30.1	36.1	44.0	10.2 (7.5)	(7.0 - 9.0)	2337	12	691
	65	255/65 R 17	110 S	SL	OWL	15506820000	Yes	30.1	37.2	44.0	10.2 (7.5)	(7.0 - 9.0)	2337	12	691
	70	245/70 R 17	110 T	SL	OWL	15506810000	Yes	30.5	36.8	44.0	9.8 (7.0)	(6.5 - 8.0)	2337	12	681
17	70	265/70 R 17	115 S	SL	OWL	15506840000	Yes	31.6	42.3	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	12	657
.,	70	LT265/70 R 17	121/118 S	E	OWL	15506650000	Yes	31.6	53.6	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	16	657
	70	LT285/70 R 17	121/118 S	Е	BSW	15506670000	Yes	32.7	58.4	80.0	11.5 (8.5)	(7.5 - 9.0)	3195	16	635
	70	LT315/70 R 17	121/118 S	Е	BSW	15506680000	Yes	34.4	66.5	65.0	12.7 (9.5)	(8.0 - 11.0)	3195	16	605
	75	LT245/75 R 17	121/118 S	E	OWL	15506640000	Yes	31.5	52.3	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	16	660
	75	255/75 R 17	115 S	SL	OWL	15506830000	Yes	32.1	40.4	44.0	10.0 (7.0)	(6.5 - 8.5)	2679	12	648
	80	LT235/80 R 17	120/117 S	E	BSW	15506610000	Yes	31.8	50.9	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	16	653
	60	245/60 R 18	105 H	SL	BSW	15578260000	Yes	29.6	32.8	44.0	9.8 (7.0)	(7.0 - 8.5)	2039	12	702
	60	265/60 R 18	110 T	SL	BSW	15574360000	Yes	30.5	38.1	44.0	10.7 (8.0)	(7.5 - 9.5)	2337	12	681
	65	265/65 R 18	114 T	SL	BSW	15506890000	Yes	31.6	39.2	44.0	10.7 (8.0)	(7.5 - 9.5)	2601	12	658
	65	275/65 R 18	116 T	SL	OWL	15506910000	Yes	32.1	42.2	44.0	11.0 (8.0)	(7.5 - 9.5)	2756	12	648
18	65	LT275/65 R 18	123/120 S	Е	OWL	15506700000	Yes	32.1	56.0	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	16	648
	70	255/70 R 18	113 T	SL	OWL	15506860000	Yes	32.1	40.6	44.0	10.2 (7.5)	(6.5 - 8.5)	2535	12	648
	70	265/70 R 18	116 S	SL	OWL	15506900000	Yes	32.6	44.1	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	12	637
	70	LT265/70 R 18	124/121 S	Е	OWL	15506690000	Yes	32.6	55.7	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	16	637
	70	LT275/70 R 18	125/122 S	Е	OWL	15506710000	Yes	33.2	58.6	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	16	627
19	55	255/55 R 19	111 V	XL	BSW	15507890000	Yes	30.0	36.7	51.0	10.4 (8.0)	(7.0 - 9.0)	2403	10	691
	50	265/50 R 20	107 T	SL	BSW	15506920000	Yes	30.4	37.7	44.0	10.9 (8.5)	(7.5 - 9.5)	2149	12	683
	55	275/55 R 20	113 T	SL	BSW	15506930000	Yes	31.9	42.3	44.0	11.2 (8.5)	(7.5 - 9.5)	2535	12	651
	55	275/55 R 20	117 H	XL	BSW	15578690000	Yes	31.9	41.4	50.0	11.2 (8.5)	(7.5 - 9.5)	2833	12	651
20	55	LT275/55 R 20	120/117 S	Е	BSW	15578700000	Yes	31.9	54.5	80.0	11.2 (8.5)	(7.5 - 9.5)	3085	16	651
20	60	LT265/60 R 20	121/118 S	E	BSW	15506720000	Yes	32.5	56.9	80.0	10.7 (8.0)	(7.5 - 9.5)	3195	16	639
	60	275/60 R 20	115 S	SL	BSW	15506940000	Yes	33.0	43.0	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	12	630
	60	LT285/60 R 20	125/122 S	E	BSW	15506740000	Yes	33.5	62.8	80.0	11.5 (8.5)	(8.0 - 10.0)	3640	16	621
	65	LT275/65 R 20	126/123 S	E	BSW	15506730000	Yes	34.1	60.6	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	16	610
22	45	285/45 R 22	114 H	XL	BSW	15506950000	Yes	32.1	42.7	51.0	11.2 (9.5)	(9.0 - 10.5)	2601	12	647
	50	275/50 R 22	115 T	XL	BSW	15578750000	Yes	32.8	41.6	50.0	11.2 (8.5)	(7.5 - 9.5)	2679	12	633

 ${\sf BSW} = {\sf Black} \; {\sf Sidewall} \; \; | \; \; {\sf OWL} = {\sf Outlined} \; {\sf White} \; {\sf Letter}$

