

# ARMOR MAX® PRO GRADE MSD® DURASEAL

MIXED SERVICE DRIVE

GOODYEAR'S BEST MIXED SERVICE DRIVE TIRE FOR  
TRACTION IN ON- AND OFF-ROAD APPLICATIONS  
WITH PUNCTURE-SEALING TECHNOLOGY



## VOCATION



Construction



Mining



Logging &  
Oil Field

## TECHNOLOGY/CERTIFICATION



DuraSeal™

## WHEEL POSITION(S)



**TOUGH, HIGH-TEAR COMPOUND IN THE TREAD** helps resist cuts, chips and tears and offers long miles to removal

**DEEP 32/32" OPEN SHOULDER TREAD DESIGN** enhances traction in mud and snow while delivering long miles to removal

**ENHANCED CASING WITH A SPECIAL MIXED SERVICE UNDERTREAD LAYER** offers enhanced casing toughness for outstanding performance through multiple retread cycles

**COOL-RUNNING BASE COMPOUND** reduces rolling resistance and improves tread and casing durability

**BUILT-IN DURASEAL TECHNOLOGY®** helps seal tread punctures\* and reduce downtime

\*Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.

ARMOR MAX® PRO GRADE MSD® MATCHING RETREADS				
RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	—	8 ½, 8 ¾, 9 ¼, 9 ½	215, 225, 240, 250	27

## Complementary Products

### ALL-POSITION

G731™ MSA  
Endurance® WHA®

G296 MSA

## Competitive Replacements

Bridgestone L320

Michelin X Works XDY

## DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM				IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	147	67	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	155	70	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68

## NON-DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING	
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM							
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	141	64	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	154	70	9.00	11.5	292	43.8	1,113	20.5	521	477	296	33	13.5	343	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	149	68	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68	

Check [goodyeartrucktires.com](http://goodyeartrucktires.com) for updated data.