

ENDURANCE®

Tow with Confidence



FEATURES

- 1. Polyester Construction Reinforced with Steel Belts
- 2. Optimized Tread Depth and Decoupling Groove
- 3. Enhanced Tread Pattern
- 4. Enhanced Inner Liner
- 5. Durawall® Technology and Scuff Guard

BENEFITS

Carries heavy-duty loads

Operate at lower temperatures when properly inflated

Tracks straight for a smooth drive

Minimizes air loss while towing

Defend against sidewall scuffs and punctures

ENDURANCE SPECIFICATIONS

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile
Endurance												
ST205/75R14	105/101N**	D	BSW	724864519	232865	5.0 - 6.5	5.5	8.0	26.1	2040	8	796
ST215/75R14	108/103N**	D	BLT	724865519	232866	5.5 - 7.0	6.0	8.5	26.7	2200	8	779
ST205/75R15	107/102N**	D	BLT	724861519	232551	5.0 - 6.5	5.5	8.0	27.1	2150	8	767
ST225/75R15	117/112N**	Е	SBL	724857519	231946	6.0 - 7.0	6.0	8.8	28.3	2830	8	735
ST235/80R16	123/119N**	E	BSW	724858519	231947	6.0 - 7.5	6.5	9.3	30.8	3420	8	676
ST235/85R16	125/121N**	Ε	BSW	724860519	231948	6.0 - 7.5	6.5	9.3	31.7	3640	8	656
ST255/85R16	129/125N**	Ε	BSW	724862519	231949	6.5 - 8.0	7.0	10.0	33.1	4080	8	629

^{**}Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.

 $Do \ not \ attempt \ to \ mount \ 16" \ rim \ diameter \ tries \ on \ 16.5" \ rim \ diameter \ wheels; \ this \ may \ result \ in \ serious \ injury \ or \ death.$

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10