

ENDURANCE® LHD® LONG HAUL DRIVE

GOODYEAR'S BEST TOUGH LONG HAUL DRIVE TIRE
FOR HIGH MILES TO REMOVAL



VOCATION



Long Haul

TECHNOLOGY/CERTIFICATION



SmartWay® Verified

WHEEL POSITION(S)



OPTIMIZED CAP BASE TREAD COMBINATION helps promote longer miles to removal and lower rolling resistance

DEEP 30/32" CLOSED SHOULDER TREAD DESIGN provides enhanced wearable rubber for long tread life

PREMIUM ENHANCED CASING helps provide toughness and durability for maximum retreadability

ADVANCED SIDEWALL COMPOUND helps promote fuel efficiency with lower rolling resistance to meet SmartWay verification

TREDLOCK® TECHNOLOGY FEATURES INTERLOCKING MICROGROOVES to help stabilize tread area for longer miles to removal and resistance to irregular wear



FEATURING
TREDLOCK
TECHNOLOGY

MATCHING RETREADS				
RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE®	295/75R22.5	8 1/2, 9, 9 1/4	215, 230, 235	26
UNICIRCLE	11R22.5	8 1/2, 9	215, 230	26
UNICIRCLE	11R24.5	8 1/2	215	26
PRECURE	—	8 1/2, 8 3/4, 9 1/4	215, 225, 235	26

Complementary Products

STEER
Endurance® LHS®

TRAILER
G316® Fuel Max® LHT®

Competitive Replacements

Bridgestone M710 Ecopia

Michelin X Line Energy D
Michelin XDA Energy +

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM				IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	126	57	8.25	11.0	279	42.3	1,074	19.9	505	492	306	30	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	126	57	8.25	11.0	279	42.4	1,077	20.0	508	491	305	30	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	131	59	8.25	11.4	290	41.3	1,049	19.3	490	508	316	30	12.9	328	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	139	63	8.25	10.9	277	44.5	1,130	20.9	531	469	291	30	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	139	63	8.25	10.8	274	44.5	1,130	20.9	531	469	291	30	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	137	62	8.25	11.1	282	42.3	1,074	19.9	505	493	306	30	12.5	318	75

Check goodyeartrucktires.com for updated data.