

# G182 RSD<sup>®</sup> REGIONAL SERVICE DRIVE

GOODYEAR'S BEST REGIONAL DRIVE TIRE FOR  
LONG MILES TO REMOVAL



## VOCATION



Utility



School Bus



Emergency



LTL



Construction



Food &  
Beverage



Pick-Up &  
Delivery

## WHEEL POSITION(S)



**INNOVATIVE TREAD COMPOUND** helps deliver long miles to removal in demanding drive applications

**DEEP 28/32" OPEN LUG TREAD DESIGN** helps enhance traction while delivering long miles to removal

**ENHANCED CASING WITH STEEL BELT PACKAGE** helps offer toughness and outstanding performance through multiple retread cycles

**MIRRORED, NON-DIRECTIONAL TREAD DESIGN** offers footprint uniformity and even wear

**TIE-BAR SHOULDER AND BLADED TREAD PATTERN** help deliver long, even wear

### G182 MATCHING RETREADS

| RETREADS  | SIZE        | AVAILABLE WIDTH    |                    | TREAD DEPTH |
|-----------|-------------|--------------------|--------------------|-------------|
|           |             | IN                 | MM                 | 32NDS       |
| UNICIRCLE | 295/75R22.5 | 8 1/2, 9           | 215, 230           | 28          |
| UNICIRCLE | 11R24.5     | 8 1/2, 9           | 215, 230           | 28          |
| UNICIRCLE | 11R24.5     | 8 1/2              | 215                | 28          |
| PRECURE   | —           | 8, 8 1/2, 9, 9 1/2 | 205, 215, 230, 240 | 26          |

### Complementary Products

**STEER/ALL-POSITION**  
Endurance RSA

**TRAILER**  
Endurance RST

### Competitive Replacements

Bridgestone M770  
Bridgestone M799

Michelin X Multi D  
Michelin XDN2  
Michelin XDE2+

| TIRE SIZE                              | LOAD RANGE | SINGLE LOAD |       | SINGLE INFLATION |     | DUAL LOAD |       | DUAL INFLATION |     | WEIGHT |    | RIM WIDTH | OVERALL WIDTH |     | OVERALL DIAMETER |       | STATIC RADIUS |     | RPM | RPK | TREAD DEPTH | MIN. DUAL SPACING |     | SPEED RATING |
|----------------------------------------|------------|-------------|-------|------------------|-----|-----------|-------|----------------|-----|--------|----|-----------|---------------|-----|------------------|-------|---------------|-----|-----|-----|-------------|-------------------|-----|--------------|
|                                        |            | LBS         | KG    | PSI              | KPA | LBS       | KG    | PSI            | KPA | LBS    | KG | IN        | IN            | MM  | IN               | MM    | IN            | MM  |     |     | 32NDS       | IN                | MM  |              |
|                                        |            |             |       |                  |     |           |       |                |     |        |    |           |               |     |                  |       |               |     |     |     |             |                   |     |              |
| TUBELESS TIRES ON 15" DROP CENTER RIMS |            |             |       |                  |     |           |       |                |     |        |    |           |               |     |                  |       |               |     |     |     |             |                   |     |              |
| 11R22.5                                | G          | 6,175       | 2,800 | 105              | 720 | 5,840     | 2,650 | 105            | 720 | 131    | 59 | 8.25      | 10.8          | 274 | 42.1             | 1,069 | 19.6          | 498 | 496 | 308 | 28          | 12.5              | 318 | 75           |
| 11R22.5                                | H          | 6,610       | 3,000 | 120              | 830 | 6,005     | 2,725 | 120            | 830 | 132    | 60 | 8.25      | 10.8          | 274 | 42.1             | 1,069 | 19.6          | 498 | 496 | 308 | 28          | 12.5              | 318 | 75           |
| 12R22.5                                | H          | 7,390       | 3,350 | 120              | 830 | 6,780     | 3,075 | 120            | 830 | 151    | 68 | 9.00      | 11.7          | 297 | 43.4             | 1,102 | 20.4          | 518 | 481 | 299 | 28          | 13.5              | 343 | 75           |
| 295/75R22.5                            | G          | 6,175       | 2,800 | 110              | 760 | 5,675     | 2,575 | 100            | 690 | 118    | 54 | 8.25      | 11.3          | 287 | 40.8             | 1,036 | 19.0          | 483 | 512 | 318 | 28          | 12.9              | 328 | 75           |
| 11R24.5                                | G          | 6,610       | 3,000 | 105              | 720 | 6,005     | 2,725 | 105            | 720 | 139    | 63 | 8.25      | 11.0          | 279 | 44.1             | 1,120 | 20.8          | 528 | 473 | 294 | 28          | 12.5              | 318 | 75           |
| 11R24.5                                | H          | 7,160       | 3,250 | 120              | 830 | 6,610     | 3,000 | 120            | 830 | 141    | 64 | 8.25      | 11.0          | 279 | 44.1             | 1,120 | 20.8          | 528 | 473 | 294 | 28          | 12.5              | 318 | 75           |

Check [goodyeartrucktires.com](http://goodyeartrucktires.com) for updated data.