

G282 MSD[®] *MIXED SERVICE DRIVE*

GOODYEAR'S BEST MIXED SERVICE DRIVE TIRE FOR LONG MILES TO REMOVAL IN ON- AND OFF- ROAD APPLICATIONS



VOCATION



Construction



Logging & Oil Field

WHEEL POSITION(S)



HIGH-MILEAGE TREAD COMPOUND AND ENHANCED TREAD VOLUME help resist cuts, chips and tears for long tire life

DEEP 28/32" OPEN LUG TREAD DESIGN helps enhance mileage as well as helps deliver off-road and wet traction

ENHANCED CASING WITH STEEL BELT PACKAGE helps offer toughness and outstanding performance through multiple retread cycles

MIRRORED, NON-DIRECTIONAL TREAD DESIGN offers footprint uniformity and even wear

G282 MSD MATCHING RETREADS				
RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE [®]	11R22.5*	8 1/2, 9	215, 230	28
UNICIRCLE	11R24.5	8 1/2, 9	215, 230	28
PRECURE	—	8 1/2, 9	215, 230	26

Complementary Products	
ALL-POSITION G751 [™] MSA	G296 [®] MSA

Competitive Replacements	
Bridgestone M799	Michelin X Works XDY

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	62	8.25	11.1	282	41.9	1,064	19.6	498	498	310	28	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.1	282	43.9	1,115	20.6	523	475	295	28	12.5	318	75

*The 11R22.5 UniCircle ring also fits 285/75R24.5 tires.

Check goodyeartrucktires.com for updated data.