

# G289® WHA® DURASEAL™

WASTE HAUL ALL-POSITION

**WASTE HAUL ALL-POSITION TIRE  
FOR LONG HOURS TO REMOVAL WITH  
PUNCTURE-SEALING TECHNOLOGY**



## VOCATION




Waste Haul

## TECHNOLOGY/CERTIFICATION



DuraSeal

## WHEEL POSITION(S)



**WASTE HAUL TREAD COMPOUND** helps enhance tread life and scrub resistance

**DEEP 24/32" TREAD DEPTH** helps to extend tread life in waste haul applications

**STEEL BELT CASING WITH DISTINCT SIDEWALL PROTECTOR RIB** helps resist sidewall scuffing in high-scrub waste haul applications to enhance casing life

**FOUR WIDE CIRCUMFERENTIAL GROOVES** help deliver all-season traction on wet, snowy or dry roads in stop/start waste haul applications

**BUILT-IN DURASEAL TECHNOLOGY** helps seal tread punctures\* and reduce downtime

\*Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.

G289® WHA® MATCHING RETREADS				
RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE®	315/80R22.5	9 ¾, 10 ¾	250, 270	26
PRECURE	—	8 ¾, 9, 9 ¾, 9 ¾, 10 ¾, 11	215, 230, 240, 250, 270, 280	26

## Complementary Products

**DRIVE**  
Workhorse® MSD®

## Competitive Replacements

Continental HAU 3 WT    Firestone FS860

## DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG		IN	IN	MM	IN	MM	IN				MM	IN	
		TUBELESS TIRES ON 15" DROP CENTER RIMS																						
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	158	72	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68

## NON-DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	151	68	9.00	12.7	323	43.1	1,095	20.0	508	484	301	24	14.0	356	68

Check [goodyeartrucktires.com](http://goodyeartrucktires.com) for updated data.