

G316[®] LHT[™] FUEL MAX[™] DURASEAL[™] LONG HAUL TRAILER

GOODYEAR'S BEST LONG HAUL TRAILER TIRE
FOR LONG MILES TO REMOVAL WITH PUNCTURE-
SEALING TECHNOLOGY



VOCATION



Long Haul



LTL

Food &
Beverage

Tanker

TECHNOLOGY/CERTIFICATION

Fuel Max[®]DuraSeal[™]SmartWay[®]
Verified

WHEEL POSITION(S)



SPECIAL TREAD COMPOUND for long miles to removal and SmartWay verification


PROTECTIVE SHOULDER COMPOUND helps guard the outer tread from accidental curb damage

PREMIUM ENHANCED CASING helps provide toughness and durability for maximum retreadability

PRESSURE DISTRIBUTION GROOVE helps promote long, even wear

BUILT-IN DURASEAL TECHNOLOGY[®] helps seal tread punctures and reduce downtime*

*Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.



FEATURING DURASEAL TECHNOLOGY

MATCHING RETREADS				
RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE [®]	11R22.5	8 ½, 9	215, 230	12
UNICIRCLE	295/75R22.5	8 ½, 9	215, 230	12
UNICIRCLE	285/75R24.5	8 ½, 9	215, 230	12
PRECURE	—	8, 8 ½, 8 ¾, 9	205, 215, 220, 230	12

Complementary Products

STEER
Endurance[®] LHS[®]

TRAILER
Endurance[®] LHD[®]

Competitive Replacements

Bridgestone R197 Ecopia | Michelin X Line Energy T

DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING	
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG		IN	IN	MM	IN	MM	IN				MM	IN		MM
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	107	49	8.25	10.9	277	41.0	1,041	19.0	483	483	300	12	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	105	48	8.25	11.1	282	39.8	1,011	18.6	472	518	322	12	12.9	328	75	

NON-DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH			OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG		IN	IN	MM	IN	MM	IN	MM				IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	101	46	8.25	10.9	277	41.0	1,041	19.0	483	483	300	12	12.5	318	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	87	39	7.50	10.1	257	36.3	922	17.1	434	568	353	13	11.3	287	81	
275/70R22.5	J	6,940	3,150	130	900	6,395	2,900	130	900	96	44	7.50	10.5	267	37.5	953	17.5	445	550	342	14	11.9	302	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	100	45	8.25	11.1	282	39.8	1,011	18.6	472	518	322	12	12.9	328	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	108	49	8.25	11.2	284	43.1	1,095	20.1	511	478	297	12	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	103	47	8.25	11.1	282	41.0	1,041	19.1	485	503	313	12	12.5	318	75	

Check goodyeartrucktires.com for updated data.