

G622 RSD[®] REGIONAL SERVICE DRIVE

GOODYEAR'S BEST REGIONAL AND URBAN TRACTION DRIVE TIRE



VOCATION



Utility



School Bus



Emergency



Pick-Up & Delivery

WHEEL POSITION(S)



TOUGH TREAD COMPOUNDS help resist excessive wear, chunking, cracking and chipping

OPEN SHOULDER TREAD DESIGN WITH AGGRESSIVE BLADING helps deliver traction in dry, wet, muddy and snowy conditions

PREMIUM ENHANCED CASING helps provide toughness and durability for maximum retreadability

TREDLOCK[®] BLADE TECHNOLOGY WITH INTERLOCKING MICROGROOVES helps stabilize the tread for high miles to removal



**FEATURING
TREDLOCK
TECHNOLOGY**

MATCHING RETREADS

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE [®]	225/70R19.5	7 1/2	190	19
UNICIRCLE	245/70R19.5	8 1/2	215	20
UNICIRCLE	295/75R22.5	8 1/2, 9	215, 230	26
UNICIRCLE	11R22.5	8 1/2, 9	215, 230	26
UNICIRCLE	12R22.5	9	230	26
UNICIRCLE	11R24.5	8 1/2	215	26
PRECURE	—	7, 7 1/2, 8, 8 1/2	180, 190, 205, 215	16
PRECURE	—	7, 7 1/2, 8, 8 1/2, 8 3/4, 9 1/4	180, 190, 205, 215, 225, 235	22

Complementary Products - 22.5"

STEER/ALL-POSITION

Endurance[®] RSA[®]

TRAILER

Endurance[®] RST

Competitive Replacements - 22.5"

Bridgestone M724F

Bridgestone M726 EL

Michelin XDS2

Michelin X Multi D

Complementary Products - 19.5"

STEER/ALL-POSITION

Endurance[®] RSA[®] ULT 19.5"Fuel Max[®] RSA[®] ULT

Competitive Replacements - 19.5"

Bridgestone M724F

Bridgestone M729F

Michelin XDS2

Michelin X Multi D

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH		OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	MM	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
225/70R19.5**	F	3,640	1,650	95	660	3,415	1,550	95	660	62	28	6.75	8.9	226	32.4	822	15.1	384	641	398	19	10.0	254	75	
225/70R19.5**	G	3,970	1,800	110	760	3,750	1,700	110	760	64	29	6.75	9.0	227	32.4	822	15.1	384	641	398	19	10.0	254	87	
245/70R19.5**	G	4,540	2,060	110	760	4,410	2,000	110	760	76	35	6.75	9.7	245	33.5	851	15.6	396	620	385	20	11.0	279	75	
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	7.50	10.2	259	40.6	1,031	19.0	483	512	318	23	11.4	290	75	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	119	54	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	139	63	9.00	11.7	297	43.3	1,100	20.3	516	482	300	26	13.5	343	75	
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	93	42	7.50	9.6	244	37.6	955	17.7	450	552	343	23	11.0	279	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	10.0	254	37.0	940	17.3	439	561	349	23	11.3	287	81	
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	101	46	7.50	10.0	254	38.9	988	18.3	465	534	332	23	11.6	295	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	114	52	8.25	11.2	284	40.8	1,036	19.1	485	512	318	26	12.9	328	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	134	61	8.25	11.1	282	43.9	1,115	20.6	523	475	295	26	12.5	318	75	

Check goodyeartrucktires.com for updated data.

**Sizes for the G622 RSD ULT.