

G751™ MSA DURASEAL

MIXED SERVICE ALL-POSITION

GOODYEAR'S BEST MIXED SERVICE
ALL-POSITION TIRE FOR LONG MILES TO
REMOVAL IN ON- AND OFF-ROAD APPLICATIONS
WITH PUNCTURE-SEALING TECHNOLOGY



VOCATION



Emergency

Logging &
Oil Field

Construction

TECHNOLOGY/CERTIFICATION



DuraSeal™

WHEEL POSITION(S)



HIGHER-SCRUB TREAD COMPOUND AND MORE WEARABLE RUBBER
help resist cuts, chips and tears and offer long miles to removal in on- and off-the-road applications

DEEP 24/32" TREAD DEPTH WITH MORE WEARABLE RUBBER VOLUME
helps put more wearable rubber on the road for enhanced mileage

ENHANCED CASING WITH STEEL BELT PACKAGE helps offer toughness and outstanding performance through multiple retread cycles

WIDER FOOTPRINT helps improve stability and traction

BUILT-IN DURASEAL TECHNOLOGY® helps seal tread punctures* and reduce downtime

*Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.

Complementary Products

DRIVE

G282 MSD®

Competitive Replacements

Bridgestone M853

Michelin X Works Z

DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM				IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	144	65	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	161	73	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68

NON-DURASEAL SIZES AVAILABLE

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH 32NDS	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM				IN	MM	
TUBELESS TIRES ON 15" DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	135	61	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	150	68	9.00	11.8	300	43.2	1,097	20.3	516	483	300	24	13.5	343	68
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	155	70	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	66	8.25	11.1	282	44.0	1,118	20.7	526	474	295	24	12.5	318	68
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	160	72	8.25	11.3	287	45.3	1,151	21.2	538	461	287	24	13.2	335	68

Check goodyeartrucktires.com for updated data.