

WRANGLER® ALL-TERRAIN ADVENTURE WITH KEVLAR®

A Versatile Tire with Rugged Strength for Quiet On-Road Driving and Going Off-Road at a Moment's Notice – Featuring DuPont™ Kevlar® Fiber and Durawall® Technology



FEATURES

1. A layer of DuPont Kevlar®
2. Durawall Technology
3. Traction ridges and open shoulder blocks
4. Biting edges and a rubber compound

BENEFITS

- Offers rugged strength for confident off-road driving
- Helps resist sidewall cuts and punctures
- Help clear mud and snow for versatile off-road traction
- Offer superior traction on wet and icy roads

60000*
MILE TREAD LIFE
LIMITED WARRANTY
95,000 Kilometer
Tread Life
Limited Warranty



All-Terrain



Severe Snow†



Rugged
Toughness from
DuPont™ Kevlar®



Chosen as Original Equipment
by Global Vehicle Manufacturers

** Compared to standard load tires.

† Select LT sizes marked with the Severe Snow Conditions Symbol.

The Three-Peak Mountain Snowflake Designation located on the sidewall of a tire indicates a tire that meets a snow traction standard set by FMVSS (Federal Motor Vehicle Safety Standards).

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company used under license by The Goodyear Tire & Rubber Company and affiliates.

*For more complete information, go to Tire-HQ™ at www.tire-hq.com or contact your Goodyear representative.

All tires include Nationwide Warranty Service and Online Tire Registration. Nationwide Warranty Service Link: https://www.goodyear.com/en_US/support/tire-warranty.html

Online Tire Registration Link: https://www.goodyear.com/en_US/support/register-tires.html

WRANGLER ALL-TERRAIN ADVENTURE WITH KEVLAR® SPECIFICATIONS

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile	UTQG	ORIGINAL EQUIPMENT FITMENT - 2024
Wrangler All-Terrain Adventure With Kevlar														
245/75R16	111T	SL	OWL	758059571	219136	6.5 - 8.0	7.0	9.8	30.5	2403	12	686	640 A B	
235/75R17	109T	SL	BSL	758089572	220536	6.0 - 8.0	6.5	9.3	30.9	2271	12	677	640 A B	
245/65R17	107T	SL	BSL	758592572	219133	7.0 - 8.5	7.0	9.8	29.5	2149	12	708	640 A B	
245/70R17	110T	SL	BSL	758060572	219137	6.5 - 8.0	7.0	9.8	30.6	2337	12	684	640 A B	
245/75R17	112T	SL	BLT	758177707	228709	6.5 - 8.0	7.0	9.8	31.5	2469	11	663	640 A B	JEEP WRANGLER (2018 - 2023)
255/65R17	110T	SL	BSL	758069572	222658	7.0 - 9.0	7.5	10.2	30.1	2337	11	691	680 A B	CHEVROLET/ GMC COLORADO / CANYON (2015 - 2022)
255/70R17	112T	SL	OWL	758067571	219144	6.5 - 8.5	7.5	10.3	31.1	2469	12	672	640 A B	
265/65R17	112T	SL	OWL	758061571	219139	7.5 - 9.5	8.0	10.7	30.6	2469	12	684	640 A B	
265/70R17	115T	SL	BSL	758042572	220308	7.0 - 9.0	8.0	10.7	31.7	2679	12	660	640 A B	
255/70R18	113T	SL	BSW	758074707	228718	6.5 - 8.5	7.5	10.2	32.1	2535	11	651	640 A B	JEEP WRANGLER (2018 - 2023)
255/70R18	116H	XL	BLT	758260845	240461	6.5 - 8.5	7.5	10.2	32.1	2756	12	651	640 A B	LAND ROVER DEFENDER (2020 - 2024)
265/60R18	110T	SL	OWL	758076571	219150	7.5 - 9.5	8.0	10.7	30.5	2337	12	685	640 A B	
265/60R18	110T	SL	VSF	758076630	226999	7.5 - 9.5	8.0	10.7	30.5	2337	12	685	640 A B	JEEP GRAND CHEROKEE (2016 - 2023)
265/65R18	114T	SL	OWL	758068571	219145	7.5 - 9.5	8.0	10.7	31.5	2601	12	663	640 A B	
265/70R18	116T	SL	OWL	758070571	219147	7.0 - 9.0	8.0	10.7	32.6	2756	12	640	640 A B	
275/65R18	116T	SL	BSL	758081572	220322	7.5 - 9.5	8.0	11.0	32.1	2756	12	651	640 A B	
275/65R18	116T	SL	OWL	758066571	219143	7.5 - 9.5	8.0	11.0	32.1	2756	12	651	640 A B	
255/65R19	114H	XL	BLT	758263845	240443	7.0 - 9.0	8.0	10.7	32.2	2601	12	649	640 A B	LAND ROVER DEFENDER (2019 - 2024)
255/60R20	113H	XL	BLT	758264845	240444	7.0 - 9.0	8.5	10.9	32.0	2535	12	653	640 A B	LAND ROVER DEFENDER (2019 - 2024)
265/50R20	107T	SL	VSF	758124630	227271	7.5 - 9.5	8.5	10.9	30.5	2149	12	686	640 A B	JEEP GRAND CHEROKEE (2016 - 2021)
275/55R20	113T	SL	BSL	758065572	219141	7.5 - 9.5	8.5	11.2	31.9	2535	12	655	640 A B	
275/55R20	113T	SL	OWL	758065571	222025	7.5 - 9.5	8.5	11.2	31.9	2535	12	655	640 A B	FORD F-150 (2015 - 2020)
275/60R20	115T	SL	BSL	758082572	220323	7.5 - 9.5	8.0	11.0	33.0	2679	12	634	640 A B	
275/60R20	115T	SL	OWL	758073571	219148	7.5 - 9.5	8.0	11.0	33.0	2679	12	634	640 A B	
Wrangler All-Terrain Adventure With Kevlar Pro-Grade														
LT215/85R16	115/112R**	E	BSL	748517572	219162	5.5 - 7.0	6.0	8.6	30.5	2680	15	688		
LT225/75R16	115/112R**	E	BSL	748748572	219159	6.0 - 7.0	6.0	8.8	29.3	2680	15	714		
LT245/75R16	120/116S**	E	BSL	748103572	225437	6.5 - 8.0	7.0	9.8	30.7	3042	15	686		
LT265/75R16	123/120R**	E	BSL	748746572	219157	7.0 - 8.0	7.5	10.5	31.7	3415	15	660		
LT235/80R17	120/117R**	E	BSL	748635572	219165	6.0 - 7.5	6.5	9.3	31.8	3085	15	654		RAM HD (2022 - 2023)
LT245/70R17	119/116R**	E	BSL	748469572	220329	6.5 - 8.0	7.0	9.8	30.6	3000	15	684		
LT245/75R17	121/118S**	E	BSL	748104572	225440	6.5 - 7.5	7.0	9.8	31.7	3195	15	663		
LT265/70R17	121/118S**	E	BSL	748661572	225843	7.0 - 8.5	8.0	10.7	31.7	3195	15	660		
LT265/70R17	121/118S**	E	OWL	748661571	225841	7.0 - 8.5	8.0	10.7	31.7	3195	15	660		
LT285/70R17	121/118R**	E	BSL	748096572	220330	7.5 - 9.0	8.5	11.5	32.8	3195	15	638		
LT265/70R18	124/121S**	E	BSL	748014572	225842	7.0 - 8.5	8.0	10.7	31.7	3525	15	638		
§ LT275/65R18	113/110S**	C	OWL	748958571	222029	7.5 - 9.0	8.0	11.0	32.1	2535	15	651		FORD F-150 (2014 - 2020)
LT275/65R18	123/120S**	E	OWL	74895571	225844	7.5 - 9.0	8.0	11.0	32.1	3415	15	651		
*LT275/70R18	125/122S**	E	OWL	748108571	225462	7.0 - 8.5	8.0	11.0	33.4	3640	15	630		
*LT275/70R18	125/122R**	E	B01	748139686	225567	7.0 - 8.5	8.0	11.0	33.2	3640	14	630		FORD SUPER DUTY (2017 - 2022)
*LT275/70R18	125/122R**	E	OWL	748139571	227769	7.0 - 8.5	8.0	11.0	33.2	3640	14	630		FORD SUPER DUTY (2017 - 2022)
LT265/60R20	121/118R**	E	BSL	748097572	220332	7.5 - 9.5	8.0	10.7	32.5	3195	15	640		
LT275/65R20	126/123S**	E	BSL	748303572	226062	7.5 - 9.5	8.0	11.0	34.1	3750	15	610		
LT285/60R20	125/122R**	E	BSL	748015572	220337	8.0 - 10.0	8.5	11.5	33.5	3640	15	622		

§ Only one layer of Kevlar®

^ 4-rib version, not marked with the Severe Snow Designation symbol

*Discontinued July 2023- February 2024

**Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10