

WRANGLER SR-A®

A Trusted Tire Offering a Smooth, Quiet Ride



FEATURES

1. Zigzag microgrooves
2. Wide circumferential grooves
3. Exclusive wet traction compound

BENEFITS

- Offer enhanced traction in rain, snow and ice
- Help move water away from the tread for enhanced traction in rain
- Helps provide traction on wet roads

50000 *

MILE TREAD LIFE
LIMITED WARRANTY

80,000 Kilometer
Tread Life
Limited Warranty
P-Metric Sizes Only



On-Road



All-Season



Chosen as Original Equipment
by Global Vehicle Manufacturers

*For more complete information, go to Tire-HQ™ at www.tire-hq.com or contact your Goodyear representative.

All tires include Nationwide Warranty Service and Online Tire Registration. Nationwide Warranty Service Link: https://www.goodyear.com/en_US/support/tire-warranty.html
Online Tire Registration Link: https://www.goodyear.com/en_US/support/register-tires.html

WRANGLER SR-A SPECIFICATIONS

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile	UTQG	ORIGINAL EQUIPMENT FITMENT- 2024
Wrangler SR-A														
P225/70R15	100S	SL	OWL	183482418	201530	6.0 - 7.5	6.5	9.0	27.4	1753	11	762	500 A B	
P255/70R16	109S	SL	OWL	183601418	201210	6.5 - 8.5	7.5	10.2	30.1	2271	12	695	500 A B	
P255/75R17	113S	SL	OWL	183107418	199747	6.5 - 8.5	7.0	10.0	32.1	2535	12	649	500 A B	JEEP WRANGLER (2013 - 2018)
P265/70R17	113R	SL	OWL	183106418	175026	7.0 - 9.0	8.0	10.7	31.7	2535	12	660	500 A B	RAM 1500 (2013 - 2023)
P265/70R17	113R	SL	VSB	183106436	175021	7.0 - 9.0	8.0	10.7	31.7	2535	12	660	500 A B	RAM 1500 (2013 - 2023)
P275/60R20	114S	SL	OWL	183934492	216827	7.5 - 9.5	8.0	11.0	33.0	2601	11	634	500 A B	RAM 1500 (2013 - 2023)
P275/60R20	114S	SL	VSB	183934436	202747	7.5 - 9.5	8.0	11.0	33.0	2601	11	634	500 A B	NISSAN TITAN (2013 - 2023)
P275/60R20	114S	SL	VSB	183934470	221505	7.5 - 9.5	8.0	11.0	33.0	2601	11	634	500 A B	RAM 1500 (2013 - 2023)

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10