

TREAD DESIGN "A"

WRANGLER TERRITORY® AT

An All-Terrain Tire Engineered for Original Equipment Fitments

FEATURES	BENEFITS
All-terrain tread pattern	Versatility and year-round traction for where your journey takes you
Multi-angle tread sipes	Aids all-season traction capabilities on and off the road
Original equipment tuned tire construction	Balanced on and off-road traction with a comfortable ride









TREAD DESIGN "B" TREAD DESIGN "C"
WRANGLER TERRITORY AT TREAD PATTERNS VARY
WITH SIZE AND APPLICATION

TREAD DESIGN "D"

TREAD DESIGN "E"





Chosen as Original Equipment by Global Vehicle Manufacturers

WRANGLER TERRITORY AT SPECIFICATIONS

								Section	Overali	wax	read			
	Service	Load		Product	Material	Approved Rim	Measuring Rim	Width	Diameter	Load	Depth			
Size	Description	Range	Sidewall	Code	Number	Widths (Inches)	Width (Inches)	(Inches)	(Inches)	(Lbs)	(in 32nds)	Revs / Mile	UTQG	ORIGINAL EQUIPMENT FITMENT- 2024
Wrangler Territory	AT													
>265/70R16	112T	SL	BSL	734070640	242884	7.0 - 9.0	8.0	10.7	31.7	2469	11	660	580 A B	TOYOTA TACOMA TRD PRO (2022 - 2023)
»225/55R17	101H	XL	BSL	734088640	244181	7.0 - 9.0	8.0	10.4	26.8	1819	12	695	400 B B	
»235/55R17	103H	XL	BSL	734090640	244182	7.5 - 9.5	8.5	10.9	30.5	1929	12	677	400 B B	
#255/70R17	112T	SL	BSL	734002640	240394	6.5 - 8.5	6.5	9.0	29.5	2469	11	710	580 B B	FORD RANGER (2023 - 2024)
#255/65R18	111T	SL	BSL	734003640	240396	7.0 - 9.0	7.5	10.2	31.1	2403	11	673	580 B B	FORD RANGER (2023 - 2024)
>265/60R18	110H	SL	BSL	734004640	237412	7.5 - 9.5	8.0	10.7	30.5	2337	12	685	580 A B	JEEP GRAND CHEROKEE (2022 - 2023)
>265/65R18	114T	SL	BSL	734006640	238905	7.5 - 9.5	8.0	10.7	31.5	2601	10	663	580 A B	CHEVROLET/ GMC SILVERADO / SIERRA (2022 - 2024)
>265/65R18	114T	SL	OWL	734006586	238903	7.5 - 9.5	8.0	10.7	31.5	2601	10	663	580 A B	CHEVROLET/ GMC SILVERADO / SIERRA (2023 - 2024)
#275/65R18	116T	SL	BSL	734001640	243142	7.5 - 9.5	8.0	11.0	32.1	2756	11	651	580 B B	FORD F-150 (2022 - 2023)
<275/60R20	116H	XL	BSL	734095640	249081	7.5 - 9.5	8.0	11.0	33.0	2756	12	633	580 A B	RIVIAN R1S / R1T (2024 - 2024)
>275/60R20	115S	SL	BSL	734087640	242633	7.5 - 9.5	9.0	11.6	33.4	2679	12	618	580 A B	CHEVROLET/ GMC TAHOE Z71 / YUKON AT4 (2022 - 2024)
^LT325/65R18	121/118T**	D	BSL	733259838	237416	9.0 - 12.0	9.5	13.0	34.8	3195	15	604		RAM 1500 TRX (2021 - 2023)
>LT265/60R22	123/120S**	Ε	BSL	733295838	246979	8.0 - 9.5	8.5	10.9	34.8	3415	12	591		CHEVROLET/ GMC SILVERADO / SIERRA (2023 - 2023)
>LT305/55R22	122/119S**	Ε	BSL	733287838	240949	9.0 - 11.0	9.5	12.5	35.5	3305	11	578		GMC HUMMER EV (2023 - 2023)

^{**}Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10

- > Tread Design "A"
- # Tread Design "B"
- ^ Tread Design "C"
- » Tread Design "D"
- < Tread Design "E"