

WRANGLER TRAILRUNNER AT®

A Tough, Dependable Tire with a Hardworking Combination of On- and Off-Road Performance



WRANGLER TRAILRUNNER AT TREAD PATTERN VARIES WITH SIZE AND APPLICATION

FEATURES	BENEFITS
1. Large interlocking tread blocks	Help to deliver strong on- and off-road durability
2. Sawtooth block edges	Offer all-season traction on and off the road
3. Multi-angle sipes	Offer all-season traction on and off the road
4. Optimized tread pattern	Enhances tread life and helps to quiet noise from on-road driving
5. Rugged stepped shoulder	Helps to provide added traction in deep mud and snow

PERFORMANCE RATINGS

Dry Traction	9
Wet Traction	9
Snow Traction	8
Off-Road Traction	8
Ride Comfort	8
Quiet Ride	8



85,000 Kilometre
Tread Life
Limited Warranty



30-Day Goodyear® Pledge
See page 11 for complete details.

ADDITIONAL POST-PURCHASE PROGRAMS:

- Nationwide Warranty Service
- Online Tire Registration



All-Terrain



Severe Snow

**



Chosen as Original Equipment
by Global Vehicle Manufacturers

* See warranty brochure for complete details.

** 5-Rib LT sizes (section width 245 and greater) marked with the Severe Snow Conditions Symbol.

WRANGLER TRAILRUNNER AT SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/MILE	UTQG	ORIGINAL EQUIPMENT FITMENT
225/75R15	102T	SL	OWL	741131680	229120	6.0 - 7.5	6	8.8	28.3	1,874	12	739	580 A B	
* 235/75R15	105S	SL	OWL	741126680	229103	6.0 - 8.0	6.5	9.3	28.9	2,039	12	723	580 A B	
235/75R15	105S	SL	BSL	741126681	240555	6.0 - 8.0	6.5	9.25	28.9	2,039	12	724	580 A B	
225/75R16	104S	SL	OWL	741129680	229109	6.0 - 7.5	6	8.8	29.3	1,984	12	713	580 A B	
235/70R16	106T	SL	OWL	741043680	229108	6.0 - 8.0	7	9.4	29	2,094	12	721	580 A B	MAHINDRA ROXOR (18-21)
245/70R16	107T	SL	OWL	741762680	229107	6.5 - 8.0	7	9.8	29.5	2,149	12	708	580 A B	
245/75R16	111S	SL	OWL	741128680	229106	6.5 - 8.0	7	9.8	30.5	2,403	12	685	580 A B	
255/70R16	111S	SL	OWL	741127680	229104	6.5 - 8.5	7.5	10.2	30.1	2,403	12	694	580 A B	
265/70R16	112T	SL	OWL	741045680	229102	7.0 - 9.0	8	10.7	30.6	2,469	12	683	580 A B	
265/75R16	116T	SL	OWL	741057680	229105	7.0 - 9.0	7.5	10.5	31.7	2,756	12	659	580 A B	
225/65R17	102T	SL	OWL	741757680	237419	6.0 - 8.0	6.5	9	28.5	1,874	12	733	580 A B	
235/65R17	104T	SL	BLK	741996681	237473	6.5 - 8.5	7	9.45	29.1	1,984	12	719	580 A B	
235/70R17	109T	XL	BLK	741134681	229124	6.0 - 8.0	7	9.4	30	2,271	12	697	580 A B	
245/65R17	107T	SL	BLK	741592681	229110	7.0 - 8.5	7	9.8	29.5	2,149	12	708	580 A B	
245/70R17	110T	SL	BLK	741060681	229112	6.5 - 8.0	7	9.8	30.6	2,337	12	683	580 A B	
255/70R17	112T	SL	OWL	741067680	229121	6.5 - 8.5	7.5	10.2	31.1	2,469	12	672	580 A B	
265/65R17	112T	SL	OWL	741061680	229113	7.5 - 9.5	8	10.7	30.6	2,469	12	683	580 A B	
265/70R17	115T	SL	OWL	741042680	228954	7.0 - 9.0	8	10.7	31.7	2,679	12	659	580 A B	
235/60R18	103T	SL	BLK	741250681	237420	6.5 - 8.5	7	9.45	29.1	1,929	12	718	580 A B	
245/60R18	105T	SL	BLK	741001681	237472	7.0 - 8.5	7	9.7	29.6	2,039	12	707	580 A B	
255/70R18	113T	SL	OWL	741074680	229118	6.5 - 8.5	7.5	10.2	32.1	2,535	12	651	580 A B	
265/60R18	110T	SL	OWL	741130680	229116	7.5 - 9.5	8	10.7	30.5	2,337	12	685	580 A B	
265/65R18	114T	SL	OWL	741068680	229117	7.5 - 9.5	8	10.7	31.5	2,601	12	663	580 A B	
265/70R18	116T	SL	OWL	741070680	229119	7.0 - 9.0	8	10.7	32.6	2,756	12	641	580 A B	
275/65R18	116T	SL	OWL	741066680	229115	7.5 - 9.5	8	11	32.1	2,756	12	651	580 A B	
275/55R20	113T	SL	BLK	741065681	229111	7.5 - 9.5	8.5	11.2	31.9	2,535	12	655	580 A B	
275/60R20	115S	SL	BLK	741178681	231393	7.5 - 9.5	8	11	33	2,679	12	633	580 A B	CHEVROLET SILVERADO (19-21), CHEVROLET TAHOE Z71 (21), GMC SIERRA (19-21), GMC YUKON AT4 (21)
285/45R22	114T	SL	BLK	741176681	237471	9.5 - 10.5	9.5	11.2	32.1	2,601	12	651	580 A B	
WRANGLER TRAILRUNNER AT LIGHT TRUCK														
31X10.50R15LT	109R	C	OWL	742510680	229100	7.0 - 9.0	8.5	10.6	30.8	2,270	15	675		
LT215/85R16	115R	E	BLK	742517681	229093	5.5 - 7.0	6	8.6	30.5	2,680	15	682		
LT225/75R16	115R	E	BLK	742748681	228960	6.0 - 7.0	6	8.8	29.3	2,680	15	710		
LT235/85R16	120R	E	BLK	742745681	228957	6.0 - 7.5	6.5	9.3	31.7	3,042	15	656		
LT245/75R16	120S	E	BLK	742103681	228955	6.5 - 8.0	7	9.8	30.5	3,042	15	682		
LT265/75R16	123R	E	OWL	742746680	228958	7.0 - 8.0	7.5	10.5	31.7	3,415	15	656		
LT285/75R16	126R	E	BLK	742138680	232619	7.5 - 9.0	8	11.3	33.1	3,750	15	628		
LT235/80R17	120R	E	BLK	742635681	229094	6.0 - 7.5	6.5	9.3	31.8	3,085	15	654		
LT245/70R17	119S	E	BLK	742120681	229091	6.5 - 8.0	7	9.8	30.6	3,000	15	680		
LT245/75R17	121S	E	BLK	742104681	229092	6.5 - 7.5	7	9.8	31.5	3,195	15	660		
LT265/70R17	121S	E	BLK	742661681	228956	7.0 - 8.5	8	10.7	31.7	3,195	15	656		
LT285/70R17	121R	E	OWL	742096680	229123	7.5 - 9.0	8.5	11.5	33	3,195	15	630		
LT265/70R18	124S	E	OWL	742014680	229122	7.0 - 9.0	8	10.7	32.6	3,525	15	638		
LT275/65R18	123S	E	OWL	742965680	229097	7.5 - 9.0	8	11	32.1	3,415	15	648		
LT275/70R18	125R	E	OWL	742646680	229096	7.0 - 8.5	8	11	33.2	3,640	15	627		
LT275/65R20	126S	E	BSL	742303681	231395	7.5 - 9.5	8.0	11.0	34.1	3,750	12	613		CHEVROLET SILVERADO HD (19-21), GMC SIERRA HD (19-21)

*Discontinued 2020

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

For more complete information, go to Tire-HQ™ at www.tire-hq.com.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10.