

KELLY EDGE AT®

A Hardworking, Quality Tire for Light Trucks and SUVs with
On-/Off-Road Traction for Everyday Driving



EDGE AT TREAD PATTERN
VARIES WITH SIZE
AND APPLICATION

FEATURES	BENEFITS
Flared tread block edges	Help shovel mud, dirt and gravel away from the tread for off-road traction
Deep tread grooves	Help evacuate water and slush from the tread for enhanced on-highway grip
Sturdy tread blocks	Help stabilize the footprint to promote long treadwear for enhanced value
Proven tread compound	Enhances wet traction on the highway and helps improve endurance for off-road terrain

50000 *
MILE TREAD LIFE
LIMITED WARRANTY

80,000 Kilometer
Tread Life
Limited Warranty



All-Terrain

*For more complete information, go to Tire-HQ™ at www.tire-hq.com or contact your Goodyear representative.

All tires include Nationwide Warranty Service and Online Tire Registration. Nationwide Warranty Service Link: https://www.goodyear.com/en_US/support/tire-warranty.html
Online Tire Registration Link: https://www.goodyear.com/en_US/support/register-tires.html

KELLY EDGE AT SPECIFICATIONS

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile	UTQG
Edge AT													
225/75R15	102S	SL	OWL	357757286	228659	6.0 - 7.5	6.0	8.8	28.3	1874	12	738	560 A B
235/70R16	106T	SL	OWL	357206286	228215	6.0 - 8.0	7.0	9.5	29.0	2094	12	721	560 A B
245/70R16	107T	SL	OWL	357762286	226571	6.5 - 8.0	7.0	9.8	29.5	2149	12	707	560 A B
245/75R16	111S	SL	OWL	357566286	225770	6.5 - 8.0	7.0	9.8	30.5	2403	12	686	560 A B
255/70R16	111S	SL	OWL	357567286	225766	6.5 - 8.0	7.5	10.2	30.1	2403	12	695	560 A B
265/70R16	112T	SL	OWL	357317286	221751	7.0 - 9.0	8.0	10.7	30.6	2469	12	682	560 A B
265/75R16	116T	SL	OWL	357292286	225768	7.0 - 9.0	7.5	10.5	31.7	2756	12	660	560 A B
245/70R17	110S	SL	BSL	357675279	228660	6.5 - 8.0	7.0	9.8	30.6	2337	12	684	560 A B
255/70R17	112S	SL	OWL	357758286	228664	6.5 - 8.5	7.5	10.2	31.1	2469	12	672	560 A B
265/65R17	112T	SL	OWL	357338286	228661	7.5 - 9.5	8.0	10.7	30.6	2469	12	684	560 A B
265/70R17	115T	SL	OWL	357747286	221714	7.0 - 9.0	8.0	10.7	31.7	2679	12	660	560 A B
265/65R18	114S	SL	OWL	357644286	228667	7.5 - 9.5	8.0	10.7	31.5	2601	12	663	560 A B
275/65R18	116T	SL	OWL	357759286	228665	7.5 - 9.5	8.0	11.0	32.1	2756	12	651	560 A B
275/55R20	113S	SL	BSL	357636279	228657	7.5 - 9.5	8.5	11.2	31.9	2535	12	655	560 A B
31X10.50R15LT	109R	C	OWL	357510286	221745	7.0 - 9.0	8.5	10.6	30.5	2270	15	685	
LT225/75R16	115/112R**	E	BSL	357468279	221734	6.0 - 7.0	6.0	8.8	29.3	2680	15	710	
*LT235/85R16	120/116R**	E	BSL	357485279	221720	6.0 - 7.5	6.5	9.3	31.7	3042	15	656	
LT245/75R16	120/116S**	E	BSL	357722279	221716	6.5 - 8.0	7.0	9.8	30.5	3042	15	682	
LT265/75R16	123/120R**	E	OWL	357475286	221732	7.0 - 8.0	7.5	10.5	31.7	3415	15	656	
LT285/75R16	126/123R**	E	OWL	357746286	228635	9.0 - 7.5	8.0	11.3	32.8	3750	15	637	
LT235/80R17	120/117R**	E	BSL	357730279	221738	6.0 - 7.5	6.5	9.3	31.8	3085	15	654	
LT245/70R17	119/116S**	E	BSL	357707279	221735	6.5 - 8.0	7.0	9.8	30.6	3000	15	679	
LT245/75R17	121/118S**	E	BSL	357727279	221736	6.5 - 7.5	7.0	9.8	31.5	3195	15	660	
LT265/70R17	121/118S**	E	BSL	357726279	221718	7.0 - 8.5	8.0	10.7	31.7	3195	15	656	
LT285/70R17	121/118R**	E	OWL	357750286	228669	7.5 - 9.0	8.5	11.5	32.8	3195	15	638	
LT275/65R18	123/120S**	E	OWL	357732286	221741	7.5 - 9.0	8.0	11.0	32.1	3415	15	648	
LT275/70R18	125/122R**	E	OWL	357511286	221740	7.0 - 8.5	8.0	11.0	33.4	3640	15	623	

*Discontinued July 2023- February 2024

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10

**Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.