

KELLY EDGE® HT

A Hardworking, Quality Tire for Light Trucks and SUVs
with All-Season Traction for Everyday Driving



FEATURES

Proven tread pattern
Broad tread grooves
Reinforced center rib
Sturdy shoulder blocks

BENEFITS

For confidence in all-season conditions and a comfortable ride
Help evacuate water and slush from the tread for enhanced grip
Enhances handling and promotes even wear
Help stabilize the tread footprint to promote long treadwear for enhanced value

60000 *
MILE TREAD LIFE
LIMITED WARRANTY

95,000 Kilometer
Tread Life
Limited Warranty
Metric Sizes Only



50000 *
MILE TREAD LIFE
LIMITED WARRANTY

80,000 Kilometer
Tread Life
Limited Warranty
LT Sizes Only



On-Road

*For more complete information, go to Tire-HQ™ at www.tire-hq.com or contact your Goodyear representative.

All tires include Nationwide Warranty Service and Online Tire Registration. Nationwide Warranty Service Link: https://www.goodyear.com/en_US/support/tire-warranty.html

Online Tire Registration Link: https://www.goodyear.com/en_US/support/register-tires.html

KELLY EDGE HT SPECIFICATIONS

Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Widths (Inches)	Measuring Rim Width (Inches)	Section Width (Inches)	Overall Diameter (Inches)	Max Load (Lbs)	Tread Depth (in 32nds)	Revs / Mile	UTQG
Edge HT													
*265/70R16	112S	SL	OWL	357564313	234242	7.0 - 9.0	8.0	10.7	30.6	2469	12	682	600 A B
245/70R17	110S	SL	OWL	357675313	234244	6.5 - 8.0	7.0	9.8	30.6	2337	12	684	600 A B
*255/70R17	112T	SL	OWL	357007313	234258	6.5 - 8.5	7.5	10.2	31.1	2469	12	672	600 A B
*265/70R17	115S	SL	OWL	357001313	234241	7.0 - 9.0	8.0	10.7	31.7	2679	12	660	600 A B
*285/45R22	114H	XL	BSL	357002297	234255	9.5 - 10.5	9.5	11.2	32.1	2601	12	651	600 A B
LT245/75R16	120/116R**	E	BSL	357469297	234249	6.5 - 8.0	7.0	9.8	30.5	3042	15	686	
LT235/80R17	120/117R**	E	BSL	357730297	234259	6.0 - 7.5	6.5	9.3	32.1	3085	15	657	
LT245/75R17	121/118R**	E	BSL	357958297	234252	6.5 - 7.5	7.0	9.8	31.5	3195	15	663	
LT265/70R17	121/118R**	E	OWL	357502313	234250	7.0 - 8.5	8.0	10.7	31.7	3195	15	660	
LT275/65R18	123/120R**	E	OWL	357965313	234260	7.5 - 9.0	8.0	11.0	32.1	3415	15	651	

*Discontinued July 2023- February 2024

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10

**Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.