

KELLY EDGE® MT

A Hardworking, Quality Tire for Light Trucks and SUVs with Maximum Traction for Off-Road Driving



| FEATURES | BENEFITS |
|-------------------------|--|
| Proven tread pattern | For off-road confidence in all-season conditions and a quiet ride |
| Multi-directional sipes | Provide enhanced handling on wet roads |
| Wide, open grooves | For digging through mud, sand and gravel, and clearing debris from the tread pattern |
| Stud-ready blocks | Deliver added traction in winter conditions when used with optional #16 metal studs |



*For more complete information, go to Tire-HQ™ at www.tire-hq.com or contact your Goodyear representative.
All tires include Nationwide Warranty Service and Online Tire Registration. Nationwide Warranty Service Link: https://www.goodyear.com/en_US/support/tire-warranty.html
Online Tire Registration Link: https://www.goodyear.com/en_US/support/register-tires.html

KELLY EDGE MT SPECIFICATIONS

| Size | Service Description | Load Range | Sidewall | Product Code | Material Number | Approved Rim Widths (Inches) | Measuring Rim Width (Inches) | Section Width (Inches) | Overall Diameter (Inches) | Max Load (Lbs) | Tread Depth (in 32nds) | Revs / Mile | Stud Pin Size (TSMI #) |
|----------------|---------------------|------------|----------|--------------|-----------------|------------------------------|------------------------------|------------------------|---------------------------|----------------|------------------------|-------------|------------------------|
| Edge MT | | | | | | | | | | | | | |
| *LT235/85R16 | 120/116Q** | E | BSL | 357605332 | 239550 | 6.0 - 7.5 | 6.5 | 9.3 | 31.7 | 3042 | 18 | 656 | 16 |
| *LT265/75R16 | 123/120Q** | E | BSL | 357610332 | 239554 | 7.0 - 8.0 | 7.5 | 10.5 | 31.7 | 3415 | 18 | 656 | 16 |
| *LT285/75R16 | 126/123P** | E | BSL | 357584332 | 239559 | 7.5 - 9.0 | 8.0 | 11.3 | 33.1 | 3750 | 18 | 628 | 16 |
| *LT235/80R17 | 120/117Q** | E | BSL | 357318332 | 239549 | 6.0 - 7.5 | 6.5 | 9.3 | 31.8 | 3085 | 18 | 654 | 16 |
| *LT245/75R17 | 121/118Q** | E | BSL | 357290333 | 239551 | 6.5 - 7.5 | 7.0 | 9.8 | 31.7 | 3195 | 18 | 656 | 16 |
| *LT265/70R17 | 121/118Q** | E | BSL | 357289332 | 239552 | 7.0 - 8.5 | 8.0 | 10.7 | 31.7 | 3195 | 18 | 656 | 16 |
| *LT285/70R17 | 121/118Q** | D | OWL | 357310333 | 239558 | 7.5 - 9.0 | 8.5 | 11.5 | 33.0 | 3195 | 18 | 630 | 16 |
| *LT315/70R17 | 121/118Q** | D | BSL | 357300332 | 239560 | 8.5 - 10.0 | 9.5 | 12.7 | 34.4 | 3195 | 18 | 605 | 16 |
| *35X12.50R17LT | 121Q | E | BSL | 357020332 | 239561 | 8.5 - 11.0 | 10.0 | 12.5 | 34.8 | 3195 | 18 | 598 | 16 |
| *LT265/70R18 | 124/121Q** | E | BSL | 357009332 | 239553 | 7.0 - 9.0 | 8.0 | 10.7 | 32.9 | 3525 | 18 | 633 | 16 |
| *LT275/65R18 | 123/120Q** | E | BSL | 357301332 | 239555 | 7.5 - 9.0 | 8.0 | 11.0 | 32.1 | 3415 | 18 | 648 | 16 |
| *LT275/70R18 | 125/122Q** | E | BSL | 357600332 | 239556 | 7.0 - 8.5 | 8.0 | 11.0 | 33.4 | 3640 | 18 | 623 | 16 |
| *LT285/65R18 | 125/122Q** | E | BSL | 357015332 | 239557 | 8.0 - 10.0 | 8.5 | 11.5 | 32.8 | 3640 | 18 | 634 | 16 |
| *35X12.50R18LT | 123Q | E | BSL | 357014332 | 239562 | 8.5 - 11.0 | 10.0 | 12.5 | 35.4 | 3415 | 18 | 587 | 16 |

*Discontinued July 2023- February 2024

Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

NOTE: When replacing a vehicle's original equipment light truck tires with passenger car tires, the load on each replacement car tire must not exceed the maximum load stamped on the replacement car tire sidewall divided by 1.10

**Max load decreases if tire is used in a dual application. For dual max load please refer to the tire sidewall.

For optimum performance, studded tires should be used in sets of four. Only new tires should be fitted with studs. Studded tires can be sold for use only where use is not prohibited by law.