

NT420V[®]

LUXURY TRUCK & SUV TIRE



*Ratings based on comparison to other Nitto product in the segment

PERFORMANCE RATED: **HWV** UTQG TREADWEAR: **460** TRACTION: **A** TEMPERATURE: **A**

■ DRY PERFORMANCE

Large outer tread blocks increase the amount of road contact surface area, improving cornering grip and performance in dry conditions.

■ EVEN WEAR

The tread's non-directional design allows for cross rotation for more even wear and a longer tread life.

*Consult your tire retailer on the appropriate rotation pattern for your vehicle.

■ REDUCED NOISE

Asymmetric sipe and groove count combined with a variable pitch tread block design work together to reduce annoying noise frequency peaks.

■ WET PERFORMANCE

Two wide circumferential grooves channel water away from the tread blocks, while the high number of inner lateral grooves provide biting edges for wet traction.

■ LT-METRIC SIZES

NT420V in LT-metric sizes are constructed to handle heavier $\frac{3}{4}$ to 1-ton trucks like heavy-duty diesel trucks.

SIZE AND SPECIFICATIONS

ALL-SEASON TRUCK & SUV TIRE

WHEEL DIAMETER

TIRE SIZE

STOCK NUMBER

TREAD DEPTH (1/32")

INFLATED DIMENSIONS Overall Dia. (in.) | Overall Width (in.)

APPROVED RIM (Measuring Rim) Width (in.)

MAXIMUM Load (lbs.) @ Press (PSI)

WEIGHT (lbs.)

20"

*265/45R20	108V XL	206790	10.3	29.37	10.47	8.5-(9.0)-10.0	2205	@	50	33.95
*265/50R20	111V XL	203090	10.3	30.47	10.91	7.5-(8.5)-9.5	2403	@	50	35.49
*275/40R20	106W XL	206740	10.5	28.66	10.94	9.0-(9.5)-11.0	2094	@	50	35.94
*275/45R20	110V XL	206770	10.5	29.76	10.75	8.5-(9.0)-10.5	2337	@	50	39.02
*275/55R20	117H XL	203920	12.2	31.89	11.18	7.5-(8.5)-9.5	2833	@	50	40.96
*275/60R20	116H XL	206750	12.2	32.99	10.98	7.5-(8.0)-9.5	2756	@	50	44.53
*285/40R20	108V XL	206990	10.6	28.98	11.42	9.5-(10.0)-11.0	2205	@	50	35.98
*285/50R20	116V XL	207640	10.6	31.26	11.69	8.0-(9.0)-10.0	2756	@	50	45.42
*295/45R20	114V XL	206780	10.7	30.47	11.65	9.5-(10.0)-11.0	2601	@	50	38.36
*305/50R20	120H XL	203950	12.5	32.05	12.44	8.5-(9.5)-11.0	3086	@	50	49.87
LT305/55R20 F	125/122S	206660	14.2	33.23	12.44	9.0-(9.5)-11.0	3640/3305	@	80	66.36
*315/35R20	110W XL	207770	11.0	28.66	12.60	10.5-(11.0)-12.5	2337	@	50	40.26
LT325/50R20 F	124S	206730	14.5	32.83	13.23	9.5-(10.0)-11.5	3525	@	80	67.02

22"

*265/35R22	102V	207650	10.3	29.33	10.67	9.0-(9.5)-10.5	1874	@	50	35.52
*265/40R22	106V	207470	10.3	30.35	10.67	9.0-(9.5)-10.5	2094	@	50	36.38
*275/35R22	104W	207720	10.5	29.57	10.94	9.0-(9.5)-11.0	1984	@	50	37.39
*275/40R22	107V	207480	10.5	30.67	10.94	9.0-(9.5)-11.0	2149	@	50	37.04
*275/45R22	112V	206980	10.5	31.77	10.75	8.5-(9.0)-10.5	2469	@	50	41.89
275/50R22	111H	207750	12.2	32.87	11.18	7.5-(8.5)-9.5	2403	@	51	41.12
*285/35R22	106W	206760	10.6	29.88	11.42	9.5-(10.0)-11.0	2094	@	50	36.60
*285/40R22	110W	207490	10.6	30.98	11.42	9.5-(10.0)-11.0	2337	@	50	38.62
*285/45R22	114H	203930	12.2	32.09	11.22	9.0-(9.5)-10.5	2601	@	50	41.40
*295/30R22	103V	207670	10.7	29.02	11.85	10.0-(10.5)-11.0	1929	@	50	37.37
*305/40R22	114H	203960	11.2	31.61	12.32	10.0-(11.0)-12.0	2601	@	50	46.61
*305/45R22	118H	203940	12.5	32.80	11.93	9.5-(10.0)-11.5	2910	@	50	47.95
LT305/50R22 F	124/121S	207740	14.1	34.06	12.44	9.0-(9.5)-11.0	3525/3195	@	80	58.86
*315/30R22	107W	207710	11.0	29.49	12.60	10.5-(11.0)-11.5	2149	@	50	40.54
LT315/45R22 F	121/118S	205690	14.4	33.19	12.40	10.0-(10.5)-12.0	3195/2910	@	80	66.14
*325/35R22	114W	207760	11.1	30.98	13.03	11.0-(11.5)-13.0	2601	@	50	42.88

24"

*285/35R24	108V	207730	10.6	31.89	11.42	9.5-(10.0)-11.0	2205	@	50	42.95
*295/35R24	110H	207680	12.3	32.13	11.85	10.0-(10.5)-11.5	2337	@	50	44.95
*305/35R24	112H	207690	12.5	32.44	12.32	10.0-(11.0)-12.0	2469	@	50	47.22

Technical specs are subject to change without notice. LT tires with a "C" load range have a 6-ply rating. LT tires with a "D" load range have an 8-ply rating. LT Tires with an "E" load range have a 10-ply rating. LT Tires with an "F" load range have a 12-ply rating. *Indicates Extra Load (XL)