

Extreme versatility takes you from peak to pavement and back with absolute authority.

FEATURES AND BENEFITS



OFF-ROAD DURABILITY

Protects against impacts and punctures for ultimate peace of mind.



LONG TREAD LIFE

Optimized contact area and unique compound provide flatter footprint and longer tread life.



QUIET RIDE

Distinctive tread grooves dramatically reduce pattern and road noise for a smooth, quiet ride in the segment.



OFF-ROAD TRACTION

Specially-engineered tread pattern provides strength and grip no matter how rugged the road.



50,000-Mile Limited Treadwear Warranty (Euro-Metric Sizes)

45,000-Mile Limited Treadwear Warranty (LT-Metric Sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
31X10.50R15 109Q	110116001	C	NA	46.3	8.5	7.0 - 9.0	10.6	30.7	8.4	17	13.6	676	2270@50	-	BW
LT235/70R16 104/101Q	110116037	C	NA	40.3	7	6.0 - 8.0	9.4	29.2	7.5	16	13.2	711	1985@50	1820@50	BW
LT235/85R16 120/116Q	110116052	E	NA	50.1	6.5	6.0 - 7.5	9.4	31.9	7.3	16	14.2	651	3042@80	2778@80	BW
LT245/70R16 118/115Q	110116053	E	NA	48.2	7	6.5 - 8.0	9.9	29.8	7.9	16	13.4	697	2910@80	2680@80	BW
245/75R16 111T	110116078	SL	500/A/B	38.3	7	6.5 - 8.0	9.8	30.5	7.5	14	13.6	682	2403@51	-	BW
265/70R16 116T	110116079	XL	500/A/B	40.5	8	7.0 - 9.0	10.8	30.6	8.1	14	13.7	678	2756@50	-	BW
LT265/70R16 121/118Q	110116054	E	NA	52.3	8	7.0 - 9.0	10.9	30.8	8.6	17	13.8	674	3195@80	2910@80	BW
LT265/75R16 123/120Q	110116002	E	NA	54.5	7.5	7.0 - 8.0	10.4	32	8.3	17	14.2	650	3415@80	3085@80	BW
LT275/70R16 119/116Q	110116055	D	NA	57.1	8	7.0 - 9.0	11.1	31.4	8.8	18	14	662	3000@65	2755@65	BW
LT285/75R16 126/123Q	110116056	E	NA	58.2	8	7.5 - 9.5	11.4	33.1	8.9	18	14.7	628	3750@80	3415@80	BW
LT315/75R16 127/124Q	110116057	E	NA	69.4	8.5	8.0 - 10.5	12.4	34.8	9.8	19	15.3	598	3860@65	3525@65	BW
235/75R17 109T	110116080	SL	500/A/B	38.8	6.5	6.0 - 8.0	9.3	30.8	7.2	14	13.9	674	2271@51	-	BW
LT235/80R17 120/117Q	110116039	E	NA	50.9	6.5	6.0 - 8.0	9.3	32.2	7.3	16	14.4	646	3085@80	2835@80	BW
LT245/70R17 119/116S	110116058	E	NA	50.4	7	6.5 - 8.0	9.9	30.8	7.8	15	13.9	674	3000@80	2755@80	BW
245/70R17 110T	110116081	SL	500/A/B	38.2	7	6.5 - 8.0	9.8	30.5	7.5	14	13.8	681	2337@51	-	BW
LT245/75R17 121/118Q	110116038	E	NA	50.9	7	6.5 - 8.0	9.6	31.8	7.7	16	14.3	653	3195@80	2910@80	BW
255/65R17 114T	110116082	XL	500/A/B	38.2	7.5	7.0 - 9.0	10.2	30	7.8	14	13.6	692	2601@50	-	BW
255/70R17 112T	110116083	SL	500/A/B	40.8	7.5	6.5 - 8.5	10.2	31.1	7.8	14	14	669	2469@51	-	BW
LT255/80R17 121/118Q	110116068	E	NA	53.2	7	6.5 - 8.5	10.1	33.3	7.7	16	14.8	624	3195@80	2910@80	BW
265/65R17 116T	110116084	XL	500/A/B	39.7	8	7.5 - 9.5	10.7	30.6	8.2	14	13.8	680	2756@50	-	BW
LT265/65R17 120/117Q	110116028	E	NA	53.1	8	8.0 - 9.5	10.9	30.7	8.6	17	13.8	676	3085@80	2835@80	BW
LT265/70R17 112/109T	110116059	C	NA	48.7	8	7.0 - 9.0	10.9	31.9	8.6	16	14.3	652	2470@50	2270@50	BW
265/70R17 115T	110116085	SL	500/A/B	42.5	8	7.0 - 9.0	10.7	31.7	8.1	14	14.2	655	2679@51	-	BW
LT265/70R17 121/118Q	110116006	E	NA	55.8	8	7.0 - 8.5	10.8	32	8.6	17	14.3	650	3195@80	2910@80	BW
LT275/70R17 114/110R	110116061	C	NA	55.2	8	7.0 - 9.0	11	32.4	8.8	17	14.5	642	2600@50	2335@50	BW
LT285/70R17 121/118S	110116063	D	NA	57.2	8.5	7.5 - 9.5	11.7	33	9.1	17	14.7	630	3195@65	2910@65	BW
LT285/70R17 121/118Q	110116007	E	NA	61.1	8.5	7.5 - 9.5	11.7	33	9.1	18	14.7	630	3195@80	2910@80	BW
LT285/75R17 121/118Q	110116064	E	NA	63.7	8	7.5 - 9.5	11.5	34	8.9	18	15.1	611	3195@80	2910@80	BW
LT295/70R17 121/118Q	110116008	E	NA	64.8	8.5	7.5 - 10.0	11.8	33.5	9.4	18	15	619	3195@80	2910@80	BW
LT305/70R17 121/118Q	110116069	E	NA	65	9	8.0 - 10.0	12.4	34	9.8	18	15.1	611	3195@65	2910@65	BW
LT315/70R17 113/110S	110116070	C	NA	61.1	9.5	8.0 - 10.5	12.7	34.6	10	17	15.4	601	2535@35	2335@35	BW
33X12.50R17 121Q	110116067	F	NA	64.8	10	8.5 - 11.0	12.6	32.8	10	19	14.6	634	3195@80	-	BW
35X12.50R17 121Q	110116003	E	NA	70.3	10	8.0 - 10.5	12.8	34.8	10	19	15.4	597	3195@65	-	BW
37X12.50R17 124Q	110116004	D	NA	76.9	10	8.5 - 11.0	13.1	36.8	10	19	16.2	565	3525@50	-	BW
37X13.50R17 121Q	110116005	E	NA	80.2	11	8.5 - 11.0	14.1	36.8	10.9	19	16.2	565	3195@65	-	BW
245/75R18 112T	110116086	SL	500/A/B	42	7	6.5 - 8.0	9.7	32.5	7.5	14	14.7	639	2469@51	-	BW
LT255/60R18 117/114Q	110116065	E	NA	51.8	7.5	7.5 - 9.0	10.4	30.4	8.3	16	13.8	683	2835@80	2600@80	BW
255/70R18 116T	110116087	XL	500/A/B	42.4	7.5	6.5 - 8.5	10.3	32	7.8	14	14.5	648	2756@50	-	BW

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
LT265/60R18 119/116Q	110116048	E	NA	53.5	8	8.0 - 9.5	10.6	30.7	8.7	17	14	676	3000@80	2755@80	BW
265/60R18 114T	110116088	XL	500/A/B	39.9	8	7.5 - 9.5	10.7	30.5	8.3	14	13.9	682	2601@50	-	BW
LT265/65R18 122/119Q	110116040	E	NA	57	8	8.0 - 9.5	10.9	31.7	8.6	17	14.4	655	3305@80	3000@80	BW
265/65R18 114T	110116089	SL	500/A/B	42	8	7.5 - 9.5	10.7	31.5	8.2	14	14.3	659	2601@51	-	BW
LT265/70R18 124/121Q	110116042	E	NA	59.6	8	7.0 - 9.0	11	32.9	8.6	17	14.8	632	3525@80	3195@80	BW
LT275/65R18 123/120Q	110116041	E	NA	60.1	8	8.0 - 9.5	11.1	32.3	8.8	18	14.6	643	3415@80	3085@80	BW
275/65R18 116T	110116090	XL	500/A/B	44.2	8	7.5 - 9.5	11	32.1	8.3	14	14.5	647	2756@50	-	BW
LT275/70R18 125/122Q	110116012	E	NA	62.4	8	7.0 - 9.0	11	33.5	8.8	18	15	620	3640@80	3305@80	BW
LT285/60R18 122/119Q	110116029	E	NA	60.5	8.5	8.5 - 10.0	11.6	31.6	9.4	18	14.3	657	3305@80	3000@80	BW
285/65R18 116T	110116091	SL	500/A/B	46.8	8.5	8.0 - 10.0	11.6	32.6	8.8	14	14.7	637	2756@51	-	BW
LT285/65R18 125/122Q	110116013	E	NA	62.4	8.5	8.5 - 10.0	11.6	32.8	9.1	18	14.8	633	3640@80	3305@80	BW
LT285/70R18 127/124Q	110116072	E	NA	62.9	8.5	7.5 - 9.5	11.6	33.6	9.4	18	15.1	618	3860@80	3525@80	BW
LT285/75R18 129/126Q	110116014	E	NA	66.1	8	7.5 - 9.5	11.5	35.1	8.9	18	15.7	592	4080@80	3750@80	BW
LT295/70R18 129/126Q	110116015	E	NA	67.7	8.5	7.5 - 10.0	11.9	34.6	9.4	18	15.5	600	4080@80	3750@80	BW
LT305/65R18 124/121Q	110116073	E	NA	65.2	9	9.0 - 11.0	12.1	34	9.8	18	15.2	611	3525@65	3195@65	BW
LT305/70R18 126/123Q	110116016	E	NA	69.9	9	8.5 - 10.0	12.4	35	9.8	18	15.6	593	3750@65	3415@65	BW
LT325/65R18 127/124Q	110116030	E	NA	73.9	9.5	9.0 - 12.0	13.1	34.8	10.5	19	15.5	598	3860@65	3525@65	BW
33X12.50R18 122Q	110116034	F	NA	64.1	10	8.5 - 11.0	12.6	32.7	10	19	14.7	636	3305@80	-	BW
33X12.50R18 118Q	110116009	E	NA	64.2	10	8.5 - 11.0	12.6	32.7	10	19	14.7	635	2910@65	-	BW
35X12.50R18 128Q	110116010	F	NA	72.8	10	8.5 - 11.0	12.5	34.7	10	19	15.5	598	3970@80	-	BW
37X12.50R18 128Q	110116071	E	NA	75.4	10	8.0 - 10.5	12.8	36.8	10	19	16.3	564	3970@65	-	BW
37X13.50R18 128Q	110116011	E	NA	80.2	11	8.5 - 11.0	13.8	36.7	10.9	19	16.3	566	3970@65	-	BW
265/60R20 112H	110116092	SL	500/B/B	43.9	8	7.5 - 9.5	10.7	32.4	8.3	14	14.9	640	2469@51	-	BW
LT265/60R20 121/118Q	110116043	E	NA	58	8	8.0 - 9.5	10.7	32.8	8.7	17	15	634	3195@80	2910@80	BW
LT275/55R20 120/117Q	110116044	E	NA	57.1	8.5	8.0 - 9.5	11.2	32.3	8.8	18	14.8	643	3085@80	2835@80	BW
275/55R20 117T	110116093	XL	500/B/B	44.8	8.5	7.5 - 9.5	11.3	31.8	8.9	14	14.6	653	2833@50	-	BW
275/60R20 116T	110116094	XL	500/B/B	45.3	8	7.5 - 9.5	11.2	33	8.5	14	15.1	630	2756@50	-	BW
LT275/65R20 126/123Q	110116022	E	NA	64.2	8	7.5 - 9.5	11.3	34.3	8.8	18	15.6	605	3750@80	3415@80	BW
LT285/55R20 122/119Q	110116032	E	NA	61.6	9	8.5 - 10.0	11.8	32.5	9.6	18	14.9	639	3305@80	3000@80	BW
LT285/60R20 125/122Q	110116033	E	NA	63.4	8.5	8.5 - 10.0	11.5	33.7	9.4	18	15.3	617	3640@80	3305@80	BW
LT285/65R20 127/124Q	110116066	E	NA	62.7	8.5	8.5 - 10.0	11.8	34.8	9.1	18	15.8	598	3860@80	3525@80	BW
LT295/55R20 123/120Q	110116075	E	NA	61.5	9.5	8.5 - 10.5	12.3	33	9.8	18	15.1	630	3415@80	3085@80	BW
LT295/60R20 126/123Q	110116046	E	NA	64.6	8.5	8.5 - 10.5	11.8	34.1	9.6	18	15.5	609	3750@80	3415@80	BW
LT295/65R20 129/126Q	110116023	E	NA	69.7	8.5	8.0 - 10.0	12	35.3	9.4	18	16	588	4080@80	3750@80	BW
LT305/55R20 121/118Q	110116024	E	NA	65.7	9.5	8.5 - 11.0	12.4	33.4	9.9	18	15.2	622	3195@65	2910@65	BW
LT315/60R20 125/122Q	110116096	E	NA	69.9	9.5	9.5 - 11.0	12.6	34.8	10.4	19	15.8	597	3640@65	3305@65	BW
LT325/60R20 126/123Q	110116031	E	NA	76.2	9.5	9.5 - 11.5	13.4	35.5	10.6	19	16	585	3750@65	3415@65	BW
33X11.50R20 118Q	110116100	E	NA	59.9	9	8.0 - 10.5	11.4	32.8	9.1	18	15	634	2910@80	-	BW
33X12.50R20 119Q	110116035	F	NA	65.6	10	8.5 - 11.0	12.7	32.7	10	19	14.9	636	3000@80	-	BW
33X12.50R20 114Q	110116017	E	NA	65.7	10	8.5 - 11.0	12.6	32.6	10	19	14.9	636	2600@65	-	BW
35X11.50R20 124Q	110116074	E	NA	64.7	9	8.0 - 10.5	11.9	34.6	9.4	18	15.7	600	3525@80	-	BW
35X12.50R20 125Q	110116036	F	NA	71.2	10	8.5 - 11.0	12.6	34.7	10	19	15.7	599	3640@80	-	BW
35X12.50R20 121Q	110116018	E	NA	71.2	10	8.5 - 11.0	12.6	34.7	10	19	15.7	598	3195@65	-	BW
35X13.50R20 121Q	110116019	E	NA	74.7	11	9.5 - 12.0	13.5	34.7	10.9	19	15.7	598	3195@65	-	BW
37X12.50R20 126Q	110116020	E	NA	76.9	10	8.5 - 11.0	12.9	36.7	10	19	16.5	566	3750@65	-	BW
37X13.50R20 127Q	110116021	E	NA	80.7	11	8.5 - 11.0	13.7	36.8	10.9	19	16.5	565	3860@65	-	BW
38X13.50R20 128Q	110116097	E	NA	82.1	11	9.5 - 12.0	13.8	37.8	10.9	19	16.9	550	3970@65	-	BW
33X12.50R22 114Q	110116047	F	NA	66.3	10	9.0 - 11.0	12.3	32.8	10.2	19	15.2	633	2600@80	-	BW



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
35X12.50R22 121Q	110116025	F	NA	71.9	10	8.5 - 11.0	12.6	34.7	10	19	16	598	3195@80	-	BW
37X12.50R22 127Q	110116026	F	NA	76.7	10	9.0 - 11.5	12.6	36.9	10	19	16.8	563	3860@80	-	BW
37X13.50R22 123Q	110116027	E	NA	81.1	11	8.5 - 11.0	13.5	36.8	10.9	19	16.8	564	3415@65	-	BW